

March 7, 2008

Electronic Mail Submission (NPDES.Generalpermits@epa.gov)
US Environmental Protection Agency
RGP-NOI Processing
Municipal Assistance Unit (CMU)
One Congress Street, Suite 1100
Boston, Massachusetts 02114-2023

Re: Notice of Intent

NPDES Remediation General Permit

Brigham House IRA 341 Mount Auburn Street

Watertown, MA

Dear Sir or Madam:

On behalf of Brigham House Associates, L.P., Tetra Tech, Inc. d/b/a Tetra Tech Rizzo (TTR) has prepared this Notice of Intent (NOI) for coverage under the National Pollutant Discharge Elimination System (NPDES) Remediation General Permit (RGP), Massachusetts General Permit (MAG910000). This NOI was prepared in accordance with the general requirements of the NPDES RGP under Federal Register, Volume 70, No. 147 and related guidance documentation provided by the U.S. Environmental Protection Agency (EPA).

The signed and completed NOI forms are attached to this letter. The following sections provide additional information relevant to this NOI.

Site Information

This NOI address the proposed discharge of treated water recovered from the sub-basement/crawlspace area at 341 Mount Auburn Street in Watertown, Massachusetts (the Site). On January 25, 2008, verbal notification was made to the Massachusetts Department of Environmental Protection (DEP) regarding the occurrence of oil (number 6 fuel oil) in water that had accumulated in the sub-basement/crawlspace area at the Site. The DEP subsequently issued Release Tracking Number (RTN) 3-27461 to the release and gave verbal authorization to perform an Immediate Response Action (IRA) under the Massachusetts Contingency Plan (MCP) (310 CMR 40.0000). Based on the findings of investigations conducted at the Site to date, it is believed that the oil release is associated

with the former storage and use of number 6 fuel oil (No. 6 oil). Available records indicate that a 15,000-gallon underground storage tank (UST) that contained fuel oil was removed from the Site by the Town of Watertown in 1993.

Discharge Information

This NPDES RGP NOI is for discharges from dewatering activities that are expected to be conducted commencing upon approval from EPA. Due to the IRA condition that has been identified, the discharge will need to commence as soon as EPA authorizes the discharge. The estimated start date is March 21, 2008. This discharge is associated with the implementation of an IRA to address a release of oil at the Site. It is believed that during periods of high groundwater table elevations water accumulates in the sub-basement/crawlspace area at the Site. This accumulated water will require periodic dewatering to mitigate potential for water/flood damage to the building structure. The accumulated water may be collected by the existing sub-basement sump pump and/or placement of additional sump pumps to recover water throughout the sub-basement/crawlspace area. The discharges are expected to be intermittent, and increase in frequency during high water table periods (spring/fall). Since a release of oil has been identified at the Site, the water will at a minimum require treatment to remove non-aqueous phase liquid (NAPL) oil. The maximum discharge flow rate for the facility will be 50 gallons per minute (GPM) over a 24-hour period (72,000 gallons per day).

The treated water will be discharged to an on-site drop inlet which discharges to the Town of Watertown municipal separate storm sewer system (MS4) which ultimately discharges to the Charles River. A drawing showing the approximate location of the on-site discharge point is attached to this NOI as Figure 1.

Receiving Surface Water Information

Effluent from the treatment system will be directed to the Town of Watertown MS4 with subsequent discharge to the Charles River. The Town of Watertown requires a Dewatering Drainage Permit for discharge to their MS4 system. A copy of the permit application is provided as an attachment to this NOI. At the discharge location the Charles River is designated a Class B water body pursuant to 314 CMR 4.00.

The estimated seven-day, ten-year low flow (7Q10) of the Charles River at the approximate location of the outfall was evaluated using the USGS on-line StreamStats stream flow assessment application. The value for the 7Q10 estimated using StreamStats is 22.8 ft³/s. A copy of the report generated by StreamStats is appended to this submittal.

Information regarding Total Maximum Daily Load (TMDL) applicable to the Charles River was evaluated via a review of the listings published in the on-line EPA database. There are no approved TMDLs for the receiving surface water. The Charles River is listed Category 5 water requiring a TMDL for unknown toxicity; priority organics; metals; nutrients; organic enrichment/low dissolved oxygen; pathogens; oil and grease; taste, odor and color; noxious aquatic plants; and turbidity.

Contaminant Information

The contaminant information presented in this NOI is based on our evaluation of a sample collected from the proposed influent (untreated water) that has accumulated in the sub-basement/crawlspace area at the Site. A release of No. 6 fuel oil at the Site has resulted in the presence of NAPL oil in the form of globules and streaks upon the surface of the water that enters the sub-basement/crawlspace area on the north side of the building. The water sample was collected from the accumulated water within the sub-basement/crawlspace. Based on the results of laboratory analysis of the accumulated water, the NAPL oil has a limited solubility in the aqueous state. Accordingly, the primary concern is NAPL oil that may accumulate at the surface of the standing water.

Based on a review of the analytical data from a sample of the proposed influent, the following NPDES RGP listed pollutants have been detected:

- Total Suspended Solids (TSS): 5 mg/L
- Total Residual Chloride (TRC): 45 μg/L

Treatment System Information

The recovered water will require treatment to remove NAPL oil, with subsequent treatment to address elevated concentrations of TSS and TRC. In general, the treatment will most often be conducted as a batch process, the water will be removed from the subbasement area, and treated to remove NAPL oil, TSS and TRC and then discharged to the on-site discharge point (drop inlet). The control of NAPL oil will be performed pursuant to the IRA Plan which will include pumping the oil-impacted water into drums or other storage containers (up to 21,000-gallons in volume) with temporary on-site storage for up to 120-days. Within the 120-day period NAPL oil will be removed via physical processes (separation and/or adsorption onto sorbent material (pads)). The accumulated NAPL oil will be segregated and containerized for management as Remediation Waste under the IRA. The storage of water is also intended to provide settlement to remove TSS. Following NAPL oil removal and settling to remove TSS, the residual water may contain elevated concentrations of TRC. A manual dechlorination step is included to treat

elevated TRC to meet effluent limits using ascorbic acid (Vitamin C) or calcium thiosulfate tablets. These dechlorination chemicals will be applied pursuant to the manufacturer's directions (ratio of 2.5:1 for ascorbic acid) to remove TRC. A Material Safety Data Sheet (MSDS) for these two chemicals is provided with the NOI.

As a contingency the treatment system may also include filtration and adsorption to provide additional treatment prior to discharge. The water may be pumped through filtration units equipped with 10-micron to 25-micron bag filters to remove excessive TSS. Following particulate removal, the water may also be pumped through two appropriately sized (400 pound to 2,000-pound) granular activated carbon (GAC) units connected in series. The treatment system provider has designed the treatment system for flows up to 50 GPM (using 2,000-pound GAC units) lesser flows can be treated with 400 pound GAC units. The treatment system will have sample ports to collect water samples from the system influent, midpoint and effluent. A flow meter (totalizer and instantaneous flow meter) will also be installed at the effluent of the treatment system. A general treatment system diagram is included as an attachment to the NOI.

Consultation with State/Federal Services

The listed Areas of Critical Environmental Concern in Massachusetts and the Endangered Species list provided in Appendix I and Appendix II of the NPDES RGP were reviewed to determine whether federally-listed endangered or threatened species or critical habitats are present at the Site or in the vicinity of the discharge. In addition, a review of the National Heritage and Endangered Species Program (NHESP) on-line database (GIS data) provided by MassGIS was reviewed to identify Endangered or Threatened Species, Essential Fish Habitat or other Critical Habitat. The results of this research were compared with the requirements identified in Appendix VII of the NPDES RGP. The results of this review identified the following:

- No Federally-listed species are located in Watertown or proximate to the proposed discharge; and
- No Federally-listed Critical Habitat areas are located in Watertown or proximate to the proposed discharge.

Considering the above findings and pursuant to Appendix VII of the NPDES RGP, this facility meets the permit eligibility criteria under "Criteria A" for coverage under the NPDES RGP since no Federally listed Endangered or Threatened Species, or Critical Habitat are located in proximity to the point where the proposed discharge reaches the receiving surface water body, and consultation with federal and/or state officials is not necessary at this time.

The listed National Historic Places (NHP) in proximity to the discharge were reviewed using the electronic data base provided by the U.S. National Parks Service (NPS) website. In addition a Site visit was performed by TTR personnel to observe the Site and the potential for impact to listed properties. The results of this review identified the following:

- Although there are properties listed by the NPS in the Town of Watertown, the
 majority are buildings or other permanent land-bound structures that are not
 located in the path of the discharge or in an area that will be impacted by the
 groundwater treatment activities at the Site. The groundwater treatment activities
 will not involve new construction that could potentially affect these listed
 properties; and
- The 341 Mount Auburn Street property is a NHP listed property (Old Watertown High School). However, the proposed groundwater treatment activities are being conducted to mitigate a release of oil at the property which will benefit the listed property. In addition, dewatering is necessary to mitigate the potential for flooding or other water damage to the property.

It is believed that the treatment and discharge of water at the Site will not cause damage, deterioration, alteration or destruction of any historic property listed by the NPS or eligible for listing. Further, we do not believe that the additional flows from the discharge to the Charles River will adversely impact the historic properties. Pursuant to Appendix VII of the NPDES RGP, this facility meets the permit eligibility criteria for coverage under the NPDES RGP, and consultation with federal and/or state officials is not necessary at this time.

Request for Coverage Under NPDES RGP

In consideration of the nature of this discharge and the requirements of the NPDES RGP, it is our opinion that the subject discharge is eligible for coverage under the NPDES RGP. Brigham House Associates, L.P. requests coverage under the NPDES RGP for the discharge of recovered water to the surface waters of the Charles River.

The attached NOI form provides the requisite information pertaining to this NOI and the appropriate signature of the facility Operator/Owner (Brigham House Associates, L.P.). In accordance with Part 1 B of the NPDES RGP, the Owner is considered "Operator" of the subject facility. TTR has been subcontracted to the Owner/Operator as an environmental consultant to aid in the preparation of this NOI. However, additional "Operators" may be designated in the future and EPA will be notified by submittal of such an administrative change via a Notice of Change. The Owner/Operator or

subsequently-designated Operators shall be responsible for any enforcement action taken or imposed by federal, state or local agencies.

Pending authorization from the EPA, discharge of treated water is scheduled to begin on or about March 21, 2008 an end date for the discharge has not been determined, however it is expected that discharge will continue as needed until the IRA can be closed with DEP.

Questions or correspondence regarding the subject discharge should be directed through Mr. Andrew Burns who may be contacted at (781) 762-4800. Please contact the undersigned at (508) 903-2000 if you have any questions regarding this NOI.

Very truly yours,

Ian S. Cannan
Project Scientist

Robert J. Ankstitus, P.E., L.S.P.

Senior Project Manager

CC: Town of Watertown, Department of Public Works
Massachusetts Department of Environmental Protection


P:\PRE-FY2008\12701000\12701003\REPORTS\NPDES.RGP\2008-03-05(NPDES.RGP).DOC


B. Suggested Form for Notice of Intent (NOI) for the Remediation General Permit


1. General site information. Please provide the following information about the site:

a) Name of facility/site: Brigham House IRA	`		Facility/site address:							
Location of facility/site: longitude: -71.169937 latitude: 42.370139	Facility SIC cod	le(s): 1522	Street: 341 Moun	nt Auburn Street						
b) Name of facility/site owner: Brigham Hous	er: Brigham House Associates, L.P. Town: Watertown									
Email address of owner: mschwendenman@	hallkeen.co	m	State:	Zip:	County:					
Telephone no.of facility/site owner: (617) 923-7	7779	<u> </u>] MA	02472 Middle						
Fax no. of facility/site owner: (617) 923-6239			Owner is (check one): 1. Fe		al					
Address of owner (if different from site):			3. Private ✓ 4. other,	f so, describe:						
Street: 320 Norwood Park South										
Town: Norwood		State: MA	Zip: 02062	County: Norfolk						
c) Legal name of operator:		Operator telep	or telephone no: (781) 762-4800							
Brigham House Ass	sociates, L.P.	Operator fax	no.: (781) 762-4841	Operator email: abi	urnes@HALLKEEN.com					
Operator contact name and title: Andrew Burne	es			:						
Address of operator (if different from owner):		Street:								
Town:		State:	Zip:	County:						
d) Check "yes" or "no" for the following: 1. Has a prior NPDES permit exclusion been granted 2. Has a prior NPDES application (Form 1 & 2C) ev 3. Is the discharge a "new discharge" as defined by 40 4. For sites in Massachusetts, is the discharge covere	er been filed for OCFR 122.2? Y	the discharge? Y Yes ✓ No	es No_✓_, if "yes," date		0					

generation of dis If "yes," please l 1. site identificat 2. permit or lices 3. state agency c	scharge? Yes \(\stacksquare \) list: tion # assigned by nse # assigned: Important to the contact information	te permitting or other action which is causing the No No 3-27461 the state of NH or MA: mediate Response Action in name, location, and telephone number: derson (978) 694-3200	f) Is the site/facility covered by any other EPA permit, including: 1. multi-sector storm water general permit? Y N ✓ , if Y, number: 2. phase I or II construction storm water general permit? Y N ✓ , if Y, number: 3. individual NPDES permit? Y N ✓ , if Y, number: 4. any other water quality related permit? Y N ✓ , if Y, number:						
2. Discharge i	information. Plea	se provide information about the discharge, (attachi	ng additional sheets as needed) including:						
a) Describe the o	discharge activities	s for which the owner/applicant is seeking coverage							
discharg	ge of wat	er recovered from baser	nent sump						
b) Provide the following information about each discharge:	following discharge points: Average flow 0.1114 Is maximum flow a design value? Y N N N N N N N N N N N N N N N N N N								
3) Latitude and l pt.4:long	longitude of each o	lischarge within 100 feet: pt.1:long71.169937 lat. 42370 long. lat	139						
4) If hydrostatic	testing, total volum	ne of the discharge (gals): 5) Is the discharge ongoing its discharge of the d	e intermittent or seasonal ? sing Yes No ?						
c) Expected date	es of discharge (mr	n/dd/yy): start_03/21/08 end unknow	n at this time						
1 .		low schematic showing water flow through the facilibuting flow from the operation, 3, treatment units.							







Notes

- System shown is a possible layout (conceptual). Actual installed layout may vary from that shown here depending on ultimate customer requirements and location restrictions.
- 2. No specific installation details are to be implied from this drawing.

The designs, information and data contained hereta is proprietary and is submitted in confidence and shall not be disclosed, used or duplicated in whote or in part for any purposes whatsower without prior written permission from Baker Corp. This document shall be returned to Baker Corp. on its demand. Receipt of this document shall be deemed to be an acceptance of the conditions specified herein.

TOLERANCE: MATERIAL: Fractions: +/- 1/16

Fractions: +/- 1/16
Decimals: .X X +/- 1/16
.XXX +/- 1/18
.XXX +/- 1/32
Angles: +/- 0*30'
Bends: +/- 2*

MATERIAL: 1/18

FINISH:

BAKER

3020 OLD RANCH PARKWAY SEAL BEACH, CA 90740-2751

70 GPM PROCESS FLOW DIAGRAM

CUSTOMER: JOB NO: _

DWG BY: J. GONZALEZ DATE: SCALE: NOTES SHEET: 1 OF: 1

CKD BY: PAUL TIBBETTS DATE: DWG NO: G9M0263 REV: _

3. Contaminant information. In order to complete this section, the applicant will need to take a minimum of one sample of the untreated water and have it analyzed for all of the parameters listed in Appendix III. Historical data, (i.e., data taken no more than 2 years prior to the effective date of the permit) may be used if obtained pursuant to: i. Massachusetts' regulations 310 CMR 40.0000, the Massachusetts Contingency Plan ("Chapter 21E"); ii. New Hampshire's Title 50 RSA 485-A: Water Pollution and Waste Disposal or Title 50 RSA 485-C: Groundwater Protection Act; or iii. an EPA permit exclusion letter issued pursuant to 40 CFR 122.3, provided the data was analyzed with test methods that meet the requirements of this permit. Otherwise, a new sample shall be taken and analyzed.

a) Based on the analysis of the sample(s) of the untreated influent, the applicant must check the box of the sub-categories that the potential discharge falls within.

Gasoline Only	VOC Only	Primarily Metals	Urban Fill Sites	Contaminated Sumps	Mixed Contaminants	Aquifer Testing
Fuel Oils (and ✓ Other Oils) only	VOC with Other Contaminants	Petroleum with Other Contaminants	Listed Contaminated Sites	Contaminated Dredge Condensates	Hydrostatic Testing of Pipelines/Tanks	Well Development or Rehabilitation

b) Based on the analysis of the untreated influent, the applicant must indicate whether each listed chemical is believed present or believed absent in the potential

discharge. Attach additional sheets as needed.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample	Analytical Method	Minimum Level (ML) of	Maximum daily	value	Avg. daily value	2
	TROOME	Trosont	(1 min- imum)	(e.g., grab)	Used (method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
1. Total Suspended Solids		✓	1	grab	SM2540D	5.00	5.00	1.36		
2. Total Residual Chlorine		✓	1	grab	Hach 8167	0.020 mg/l	45	1.23E-2		
3. Total Petroleum Hydrocarbons	√	Description of the second of t	1	grab	1664	1.0 mg/l	0	0	0	0
4. Cyanide	✓		1	grab	335.4	0.0100 mg/l	0	0	0	0
5. Benzene	1		1	grab	624	1.0 ug/l	0	0	0	0
6. Toluene	1		1	grab	624	1.0 ug/l	0	0	0	0
7. Ethylbenzene	1		1	grab	624	1.0 ug/l	0	0	0	0
8. (m,p,o) Xylenes	√		1	grab	624	2.0 ug/l and 1.0 ug/l	0	0	0	0
9. Total BTEX4	√		1	grab	624	see above	0	0	0	0

⁴BTEX = Sum of Benzene, Toluenc, Ethylbenzene, total Xylenes.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method	Minimum Level (ML) of	Maximum daily	value	Avg. daily value	е
			(1 min- imum)	grab)	Used (method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
10. Ethylene Dibromide ⁵ (1,2- Dibromo-methane)	√		1	grab	504.1	0.0100 ug/l	0	0	0	0
11. Methyl-tert-Butyl Ether (MtBE)	1		1	grab	624	1.0 ug/l	0	0	0	0
12. tert-Butyl Alcohol (TBA)	√									
13. tert-Amyl Methyl Ether (TAME)	√									
14. Naphthalene	√		1	grab	8270C	2.78 ug/l	0	0	0	0
15. Carbon Tetra- chloride	√		1	grab	624	1.0 ug/l	0	0	0	0
16. 1,4 Dichlorobenzene	√		1	grab	624	1.0 ug/l	0	0	0	0
17. 1,2 Dichlorobenzene	√		1	grab	624	1.0 ug/l	0	0	0	0
18. 1,3 Dichlorobenzene	√		1	grab	624	1.0 ug/l	0	0	0	0
19. 1,1 Dichloroethane	✓		1	grab	624	1.0 ug/l	0	0	0	0
20. 1,2 Dichloroethane	✓		1	grab	624	1.0 ug/l	0	0	0	0
21. 1,1 Dichloroethylene	✓		1	grab	624	1.0 ug/l	0	0	0	0
22. cis-1,2 Dichloro- ethylene	1		1	grab	624	1.0 ug/l	0	0	0	0
23. Dichloromethane (Methylene Chloride)	√		1	grab	624	10.0 ug/l	0	0	0	0
24. Tetrachloroethylene	√		1	grab	624	1.0 ug/l	0	0	0	0

⁵EDB is a groundwater contaminant at fuel spill and pesticide application sites in New England.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method Used	Minimum Level (ML) of Test	Maximum daily	value	Avg. daily Valu	e
			(1 min- imum)	grab)	(method #)	Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
25. 1,1,1 Trichloroethane	✓		1	grab	624	1.0 ug/l	0	0	0	0
26. 1,1,2 Trichloroethane	√		1	grab	624	1.0 ug/l	0	0	0	0
27. Trichloroethylene	✓		1	grab	624	1.0 ug/l	0	0	0	0
28. Vinyl Chloride	✓		1	grab	624	1.0 ug/l	0	0	0	0
29. Acetone	√		1	grab	624	20.0 ug/l	0	0	0	0
30. 1,4 Dioxane	√									
31. Total Phenols	√		1	grab	8270C	2.78 to 5.56 ug/l	0	0	0	0
32. Pentachlorophenol	√		1	grab	8270C	2.78 ug/l	0	0	0	0
33. Total Phthalates ⁶ (Phthalate esthers)	✓									
34. Bis (2-Ethylhexyl) Phthalate [Di- (ethylhexyl) Phthalate]	√			·						
35. Total Group I Polycyclic Aromatic Hydrocarbons (PAH)	✓		1	grab	8270C	see below	0	0	0	0
a. Benzo(a) Anthracene	√		1	grab	8270C	2.78 ug/l				
b. Benzo(a) Pyrene	1		1	grab	8270C	2.78 ug/l				
c. Benzo(b)Fluoranthene	√		1	grab	8270C	2.78 ug/l				
d. Benzo(k) Fluoranthene	√		1	grab	8270C	2.78 ug/l				
e. Chrysene	√		1	grab	8270C	2.78 ug/l	0	0	0	0

⁶The sum of individual phthalate compounds.

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method Used	Minimum Level (ML) of	Maximum daily v	alue	Average daily value	
			(1 min- imum)	grab)	(method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
f. Dibenzo(a,h) anthracene	√		1	grab	8270C	2.78 ug/l				
g. Indeno(1,2,3-cd) Pyrene	√		1	grab	8270C	2.78 ug/l				
36. Total Group II Polycyclic Aromatic Hydrocarbons (PAH)	/		1	grab	8270C	2.78 ug/l	0	0	0	0
h. Acenaphthene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
i. Acenaphthylene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
j. Anthracene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
k. Benzo(ghi) Perylene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
l. Fluoranthene	1		1	grab	8270C	2.78 ug/l	0	0	0	0
m. Fluorene	1		1	grab	8270C	2.78 ug/l	0	0	0	0
n. Naphthalene-	√		1	grab	8270C	2.78 ug/l	0	0	0	0
o. Phenanthrene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
p. Pyrene	✓		1	grab	8270C	2.78 ug/l	0	0	0	0
37. Total Polychlorinated Biphenyls (PCBs)	1		1	grab	608	0.211 ug/l	0	0	0	0
38. Antimony	✓									
39. Arsenic	✓		1	grab	200.7	0.0040 mg/l	0	0	0	0
40. Cadmium	✓		1	grab	200.7	0.0025 mg/l	0	0	0	0
41. Chromium III	√		1	grab	200.7	0.0080 mg/l	0	0	0	0
42. Chromium VI	√		1	grab	SM3500CrD	0.008 mg/l	0	0	0	0

PARAMETER	Believe Absent	Believe Present	# of Samples	Type of Sample (e.g.,	Analytical Method	Minimum Level (ML) of	Maximum daily	value	Avg. daily value	
			(1 min- imum)	grab)	Used (method #)	Test Method	concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
43. Copper	✓									
44. Lead	1									
45. Mercury	√									
46. Nickel	√									
47. Selenium	\checkmark								·	
48. Silver	√ √									
49. Zinc	✓									
50. Iron	✓		1	grab	200.7	0.0550 mg/l	0	0	0	0
Other (describe):										

Step 1: Do any of the metals in the influent have a reasonable potential to exceed the effluent limits in Appendix III (i.e., the limits set at zero to five dilutions)? Y N	If yes, which metals?
Step 2: For any metals which have reasonable potential to exceed the Appendix III limits, calculate the dilution factor (DF) using the formula in Part I.A.3.c) (step 2) of the NOI instructions or as determined by the State prior to the submission of this NOI. What is the dilution factor for applicable metals? Metals: DF: 206	Look up the limit calculated at the corresponding dilution factor in Appendix IV. Do any of the metals in the influent have the potential to exceed the corresponding effluent limits in Appendix IV (i.e., is the influent concentration above the limit set at the calculated dilution factor)? Y If "Yes," list which metals:

4. I reatment system informa	tion. Please de	scribe the treatme	nt syst	em using separa	ite sheets a	s necessar	y, including:				
a) A description of the treatm	ent system, incl	uding a schematic	ofthe	proposed or ex	isting treat	tment syste	em;				
b) Identify each applicable	Frac. tank 🗸	Air stripper		Oil/water sep	arator	✓	Equalization tanks		Bag filter 🗸	C	GAC filter 🗸
treatment unit (check all that apply):	Chlorination	Dechlorination	on 🗸	Other (please	describe):						
c) Proposed average and ma Average flow rate of discharg		t es (gallons per m Maximum flow i				_	v rate(s) (gallons per sign flow rate of trea			nt syst	tem:
d) A description of chemical	additives being	used or planned to	o be us	ed (attach MSD	S sheets):	see MS	DS for dechloring	nation	chemical/ta	ablet	is
5. Receiving surface water(s)	. Please provid	information abo	ut the r	eceiving water	s), using s	eparate she	eets as necessary:				
a) Identify the discharge path	way:	Direct	With	in facility 🗸	Storm dr	ain	River/brook_	Wetl	ands	Othe	er (describe):
b) Provide a narrative descrip discharge to on-site de						_		les R	iver		
c) Attach a detailed map(s) in 1. For multiple discharges, no 2. For indirect dischargers, in The map should also include mapping), such as surface wa	imber the discha dicate the locati the location and	rges sequentially. on of the discharg distance to the no	ge to th earest s	e indirect conv anitary sewer a	eyance and	the discha	-	eptors (l	based on USGS	topog	graphical
d) Provide the state water qua	lity classification	n of the receiving	g water	Class B							
e) Provide the reported or cal Please attach any calculation						22.8		_cfs			
f) Is the receiving water a list Is there a TMDL? Yes				ted water? Yes			, for which pollutant(wn loxicity; priority organics; meta	is; nutrients;	; organic enrichment/tow DO;

6. Results of Consultation with Federal Services: Please provide the following information according to requirements of Part I.B.4 and Appendices II and VII.
a) Are any listed threatened or endangered species, or designated critical habitat, in proximity to the discharge? Yes No Learn N
b) Are any historic properties listed or eligible for listing on the National Register of Historic Places located on the facility or site or in proximity to the discharge? Yes No Have any state or tribal historic preservation officer been consulted in this determination (Massachusetts only)? Yes No No
7. Supplemental information. :
Please provide any supplemental information. Attach any analytical data used to support the application. Attach any certification(s) required by the general permit.
8. Signature Requirements: The Notice of Intent must be signed by the operator in accordance with the signatory requirements of 40 CFR Section 122.22, including the following certification: I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, I certify that the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I certify that I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.
Brigham House IRA Operator signature: ALLIGATION Operator signature: Operator sign
Actual Brances
Managing Partner Managing Partner
- 3/10/2008


	Receiving	Water In	formation		
				•	
•					
	·				-
•					

DEPARTMENT OF PUBLIC WORKS TOWN OF WATERTOWN, MASSACHUSETTS

APPLICATION FOR A DEWATERING DRAINAGE PERMIT

The undersigned,	being the	Owner	
	<u></u>	(Owner, Owner's Agent)	
of the property located at_		Mount Auburn Street	. does
	(Number)	(Street)	, accs
Residence	discharge dewat during an	ttering drainage to the public sewer to serve the Immediate Response Action and NPDES RGP	
at said location.		(Residence, Commercial Building, etc.)	
l. The following indicate	d substance(s) v	will be discharge from the proposed construction area into the sewe	r:
Substan treated wat	er recove	red from basement sump Substance	
water to be	treated to	o remove Number 6 fuel oil	
see attached	for addit	ional data	
	· · · · · · · · · · · · · · · · · · ·		
pecify other substances_			
. The maximum number	of days dischar	ge will occur. until IRA conditions are abated	i
. Beginning on March	21 2008	and ending on unknown at this time	
. The name and address of Brigham House	of perso n or firm se Associa	n who will perfrom the proposed work is ates, L.P. see attached for additional in	nforma
Plans and specifications consideration of the grant To accept and abide by	for the method ting of this perm	n who will perfrom the proposed work is ates, L.P. see attached for additional in the desired desired description of dewatering drainage discharge are attached hereunto as Exhibit wit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Proposition and the second regulations for discharge into and for the Use of Proposition and the second regulations for discharge into and for the Use of Proposition and the second regulations for discharge into and for the Use of Proposition and the second regulation and regulation and the second regulation and regulation and regulation and regulation and regulation and regulation regulation and regulation and regulation and regulation regulation and regulation regulation regulation and regulation regulation regulation regulation regulations for discharge into and for the second regulation	"A",
Plans and specifications consideration of the grant To accept and abide by	for the method ting of this perm	of dewatering drainage discharge are attached hereunto as Exhibit	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future.	s for the method ting of this perm all provisions of Waterlown, Mas	of dewatering drainage discharge are attached hereunto as Exhibit nit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Passachusetts, and of all other pertinent rules and regulations that may	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building	is for the method ting of this perm all provisions of Waterlown, Mas is sewer at no exp	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Passachusetts, and of all other pertinent rules and regulations that may appears to the Town.	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building To notify the Superintent but before any portion of	is for the method ting of this perm all provisions of Watertown, Mas I sewer at no exp dent when the b f the work is cov	of dewatering drainage discharge are attached hereunto as Exhibit nit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may tree to the Town. Species to the Town.	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building To notify the Superintent but before any portion of	is for the method ting of this perm all provisions of Waterlown, Mas is sewer at no exp	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repeate to the Town. Signed A. R.	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building To notify the Superintent but before any portion of	is for the method ting of this perm all provisions of Watertown, Mas I sewer at no exp dent when the b f the work is cov	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repense to the Town. Signed All Rules and connection to the public wered. Signed All Rules. (Applicant)	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building To notify the Superintent but before any portion of	is for the method ting of this perm all provisions of Watertown, Mas I sewer at no exp dent when the b f the work is cov	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repeate to the Town. Signed	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of Vadopted in the future. To maintain the building To notify the Superintenbut before any portion of the Server of the Town of the Server of t	is for the method ting of this permall provisions of Waterlown, Mass sewer at no expect when the best the work is control of 2009	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repense to the Town. Signed All Rules and connection to the public wered. Signed All Rules. (Applicant)	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of Vadopted in the future. To maintain the building To notify the Superintenbut before any portion of the Server of the Town of the Server of t	is for the method ting of this perm all provisions of Watertown, Mas I sewer at no exp dent when the b f the work is cov	of dewatering drainage discharge are attached hereunto as Exhibit nit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repeate to the Town. Signed / L. R. L. (Applicant) 341 Mount Auburn Street (Address of Applicant)	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of Vadopted in the future. To maintain the building To notify the Superintenbut before any portion of the Server of the Town of the Server of t	is for the method ting of this permall provisions of Waterlown, Mass sewer at no expected when the bound of the Work is considered.	of dewatering drainage discharge are attached hereunto as Exhibit nit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repeate to the Town. Signed / Certification by Town Treasurer)	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of Vadopted in the future. To maintain the building To notify the Superinten but before any ponion of the state of the series of the Town of Vadopted in the future. To maintain the building To notify the Superinten but before any ponion of the series of	is for the method ting of this permall provisions of Waterlown, Mass sewer at no expected when the bound of the Work is considered.	of dewatering drainage discharge are attached hereunto as Exhibit mit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may spense to the Town. Signed	"A",
Plans and specifications consideration of the grant To accept and abide by a Sewers of the Town of V adopted in the future. To maintain the building To notify the Superinten but before any portion of the sterming the service of the service of the terminate of the service of	is for the method ting of this permall provisions of Waterlown, Mass sewer at no expected when the bound of the Work is considered.	of dewatering drainage discharge are attached hereunto as Exhibit nit, the undersigned agrees: If the Rules and Regulations for discharge into and for the Use of Pressachusetts, and of all other pertinent rules and regulations that may repeate to the Town. Signed / Certification by Town Treasurer)	"A",

USGS MA StreamStats Page 1 of 1





StreamStats

Streamflow Statistics Report

Date: Wed Mar 5 2008 11:23:45 Site Location: Massachusetts Drainage Area: 273.89 mi2

Latitude (NAD83): 42.3640 (42 21 50) Longitude (NAD83): -71.1840 (-71 11 02)

Low Flow Basin Characteristics			
100% Statewide Low Flow (274 mi2)			
Parameter	Value	Min	Max
Drainage Area (square miles)	274 (above max value 149)	1.61	149
Mean Basin Slope from 250K DEM (percent)	2.33	0.32	24.6
Stratified Drift per Stream Length (square mile per mile)	0.22	0	1.29
Massachusetts Region (dimensionless)	0	0	1


Warning: Some parameters are outside the suggested range. Estimates will be extrapolations with unknown errors.

Streamflow Statistics									
0		Prediction Error	Equivalent	90-Percent Prediction Interval					
Statistic	Flow (ft ³ /s)	(percent)	years of record	Minimum	Maximum				
D50	293								
D60	240								
D70	164								
D75	133								
D80	104								
D85	82.8								
D90	64								
D95	43.2								
D98	28.8								
D99	23.8								
Low-Flow Statistics				of New Co.					
M7D2Y	46.4								
AUGD50	88.8								
M7D10Y	22.8								


Massachusetts Category 5 Waters "Waters requiring a TMDL"

NAME	SEGMENT ID	DESCRIPTION	SIZE	POLLUTANT NEEDING TMDL [EPA APPROVAL DATE-DOCUMENT CONTROL NUMBER]
Charles River (7239050)	MA72-08_2006	(Charles Basin) Watertown Dam, Watertown to Science Museum, Boston.	8.5 miles	-Cause Unknown -Unknown toxicity -Priority organics -Metals -Nutrients -Organic enrichment/Low DO -Pathogens -Oil and grease -Taste, odor and color -Noxious aquatic plants -Turbidity
Cheese Cake Brook (7239100)	MA72-29_2006	Headwaters, West Newton to confluence with Charles River, Newton.	1.4 miles	-Nutrients -Siltation -Organic enrichment/Low DO -(Other habitat alterations*) -Pathogens -Oil and grease -Taste, odor and color -Noxious aquatic plants
Echo Lake (72035)	MA72035_2006	Milford/Hopkinton		-Metals
Factory Pond (72037)	MA72037_2006	Holliston		-Noxious aquatic plants -(Exotic species*)
Franklin Reservoir Northeast (72095)	MA72095_2006	Franklin		-Noxious aquatic plants -Turbidity
Franklin Reservoir Southwest (72032)	MA72032_2006	Franklin	13.0 acres	-Noxious aquatic plants -Turbidity
Fuller Brook (7239625)	MA72-18_2006	Headwaters south of Route 135, Needham to confluence with Waban Brook, Wellesley.		-Cause Unknown -Organic enrichment/Low DO -(Other habitat alterations*) -Pathogens -Noxious aquatic plants
Hardys Pond (72045)	MA72045_2006	Waltham	42.8 acres	-Nutrients -Noxious aquatic plants -Turbidity -(Exotic species*)
Houghton Pond (72050)	MA72050_2006	Holliston	17.5 acres	-Noxious aquatic plants -Turbidity -(Exotic species*)
Jamaica Pond (72052)	MA72052_2006	Boston	66.7 acres	-Nutrients -Organic enrichment/Low DO
Jennings Pond (72053)	MA72053_2006	Natick	7.4 acres	-(Flow alteration*) -Noxious aquatic plants
Kendrick Street Pond (72055)	MA72055_2006	Needham	39.3 acres	-Turbidity
Linden Pond (72063)	MA72063_2006	Holliston	1.3 acres	-Noxious aquatic plants -Turbidity

98



Map Output Page 1 of 1



No filter

Include filter in navigation

140 11	itei					inci	ude filter in navigation
Row	STATE Þ	COUNTY	RESOURCE NAME	ADDRESS ▷	CITY 1	LISTED !	MULTIPLE >
1	MA	Middlesex	Browne, Abraham, House	562 Main St.	Watertown	1990-03-09	First Period Buildings of Eastern Massachusetts TR
2	MA	Middlesex	Commanding Officer's Quarters, Watertown Arsenal	443 Arsenal St.	Watertown	1976-10-07	
3	MA	Middlesex	Fowle, Edmund, House	26-28 Marshall St.	Watertown	1977-11-11	
4	MA	Middlesex	Pratt, Miles, House	106 Mt. Auburn St.	Watertown	1985-05-09	
5	MA	Middlesex	Town Diner	627 Mount Auburn St.	Watertown	1999-09-22	Diners of Massachusetts MPS
6	MA		Watertown Arsenal Historic District	Arsenal St.	Watertown	1999-05-14	
7	MA	Middlesex	Watertown High School, Old	341 Mount Auburn St.	Watertown	2006-09-22	











,	Additional Infor	mation and Calculations	
			-

Table 1. Summary of Potential Compounds in Influent Water

Chemical	Effluent Limit (μg/l)	Max. Conc. (μg/l)	Max. Mass (lbs/day) ³	Max. Mass (mg/day) ⁴	Max. Mass (kg/day) ⁴
TRC	11	45	0.0270	12,257	1.23E-02
TSS	30,000	5,000	3.0024	1,361,866	1.36E+00

Notes:

- 1. Flow rate is 50 gpm (0.072 MGD)
- 2. Assume mass of water is 8.34 lbs/gal
- 3. Lbs/day = [(ug/l/1,000)x(flow rate)x8.34 lbs/gal] 4. Assume 1 lbs = 0.45359237 kg

	57	7		ļ	-	1	-	/	4/6		-		_																								_
H	/i [(uti	01	 	ra	(10	 	10	410	U 1	671	<u></u>	<u> </u>			ļ			· .					ļ									-				_
-	D	F	=	7	o i	+ (-		Q	1	-																		[_				+	
			-		00	- 9	₹ € .) Ge	<u> </u>	<u> </u>		ļ							<u>.</u>				-	ļ							-					-
Q	=	n	ΙΛχ	1	Your	-	1	de	ch	uz	-	=		0.	1//	4	f	¥ 3	/	20					 -							\dashv		-		-	-
	-		ì	Ì	1		ĺ)	Í		Ì	•	ĺ			İ																					
Q۶	_=	7	Q	10	(ous	-1	lon	2	0	6	_/	Pel	ìe	م زال	ļ 15	4	bit	e																		
		tro	n.		> -√6	200	5	tat	<u>\$</u>	1	<u> </u>	2	3	8		4-	/5	ec	ļ 																	_	_
			-	<u> </u>	 		-	-		ļ	ļ		<u> </u>			ļ			<u> </u>					-	ļ.,	 											
	Ω	F		1	2./	114	+	<u>D</u>	3.8			1	//	14	ļ										-										-		~
	ł			İ		1	<u> </u>	no I		ير_ إ	//	U.	177						-					-												-+	
	P	F	=	(30	6				 	 								-	 				 											\dashv	_	
	1			1													_		-		_																
	D,	<u>/υ</u>	101		Ka	19	<u>e</u>	=		7	10	0	L	\mathcal{L}	zili/	19	Vc	14			10	m		A	020	ra	\times		11								
							<u> </u>	ļ	ļ	<u> </u>					<u></u>									ļ'		<u> </u>									1	_	
																								-	<u> </u>										\dashv		
$\vdash \dashv$							 -			-														-	-										\dashv		_
$\vdash \vdash$								-			<u> </u>													-	-	-	-						_				
							***************************************				<u> </u>												<u> </u>	 	-											-	
								 -															·		<u> </u>												
																			-					<u> </u>		-	 			-						\neg	
							<u> </u>																														
							ļ				<u> </u>	ļ	<u> </u>									<u> </u>	<u> </u>		ļ	ļ										\rightarrow	
																							<u> </u>		ļ		ļ	 						~~			
	-										ļ 								-	ļ			-	-						<u> </u>						_	
				~				<u> </u>	 				ļ <u>.</u>										<u> </u>	╁	-	-	-	<u> </u>			 				$\vdash \dashv$		
								ļ	-			~~ ~									 	ļ	 	╁	╁┈	<u> </u>	¦		ļ <u>.</u>								
																							╁	1	\vdash		 		<u> </u>		 						
_								ļ								<u></u>							ļ	<u> </u>	ļ	ļ	ļ	ļ		<u> </u>	ļ	ļ					_
							ļ	<u> </u>					ļ				ļ		-	<u> </u>		<u> </u>	-	<u> </u>	<u> </u>	<u> </u>	-		<u> </u>	-	<u> </u>	-	-	_			_
\vdash	-							_	-	_		-	ļ		ļ		<u> </u>			1	ļ			-	ļ	ļ	 	<u> </u>	<u> </u>		-	-	<u> </u>	-			
::::						· ··		ļ			ļ							_		1			 - -	-	-	-		<u> </u>	<u> </u>	 	-	1	 		ļ		
											<u> </u>		<u> </u>					ļ	-	 			 	+-	-	-		 -		-	-	-	-	-	-		
								ļ			 	 -		<u> </u>		\vdash	 			 	 		1	+-	1	<u> </u>	<u> </u>	\dagger	1	†	\dagger		-	-	†	<u> </u>	
																									†									İ			
																										\prod							I				
				-			ļ	1	ļ		<u> </u>	<u> </u>		<u> </u>			<u> </u>																				
							-	1	<u> </u>											ю	В	1	27	z0.	0	<u>3`</u>											
							ļ	<u> </u>	<u> </u>	ے ا		-								Sŀ	1EET	NC). <u></u>			1							OF_			<u></u>	_
\dashv	1	\dashv						 		{ 	R	; 1	ΓEΤ	'R/	\ TI	EC	1 R	IZ7	20	C/	ALCU	LAT	ED	BY_		1	<u> </u>						_DAT	re Z	3-5-	<u>.0</u> 5	
-							-		-	١		ر								CI	ŧECi	ŒD	BY.										. DAT	ΓE			
$\mid \neg \uparrow \mid$							-	 	 -	1										so	ALE		1	17	5												
<u> </u>		- 1	t				1	1		_												,		·····	·····												

MATERIAL SAFETY DATA SHEET





MSDS Number: Revision date: Revision number:

V322N 05/24/01 001 Page 1 of 2

Manufacturer:

Integra Chemical Co. 710 Thomas Ave SW Renton WA 98055 425.277.9244

24 Hour Emergency Response Telephone: 800-451-8346

PRODUCT IDENTIFICATION

Product Name:

Vita-D-Chlor

Synonyms:

Dechlorinator

Chemical formula: Proprietary

Chemical family:

Organic acid

Product number:

V322.50

HAZARD OVERVIEW

HMIS Rating: 0-1-0-B

NPFA: None established

Warning Label: Caution. Use safe chemical handling practices. Keep container closed. Use with adequate ventilation.

Avoid breathing dust. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling.

COMPOSITION/INFORMATION ON INGREDIENTS

ACGIH TLV/TWA

OSHA PEL/TWA

Organic acid

Not listed

Not listed

PHYSICAL DATA

Boiling point: Melting point: NA 192C Vapor pressure: NA Vapor density:

NA

Appearance and Odor: Odorless, fine white crystals.

Specific gravity: 1.65 (Water=1)

Evaporation rate: NA

Solubility: 33g/100mL water @25C

pH (1% solution): 2-3

FIRE AND EXPLOSION DATA

Flash point: NA

Auto-ignition temperature: NA

Flammable limits (% by volume in air): Upper: NA, Lower: NA Fire extinguishing media: Water spray, CO2, dry chemical, or foam

Special firefighting procedures: Use water to cool nearby containers and structures. Wear full protective equipment, including

suitable respiratory protection.

Unusual fire and explosion hazards: As with most organic solids, combustion is possible at elevated temperatures.

HEALTH HAZARD INFORMATION

Effects of overexposure:

Contact:

Contact may cause skin or eye irritation.

Inaestion:

No harmful effects expected.

Chronic effects of overexposure:

Inhalation: Inhalation may irritate the nose, throat and upper respiratory tract.

Exposure limits:

None identified None established

Toxicity data:

No information available

Medical conditions

aggravated by exposure:

None identified

Target organs:

None identified

Reproductive effects:

None identified

Carcinogenicity:

No listings by NTP, IARC, or OSHA

EMERGENCY FIRST AID PROCEDURES

Skin contact: Wash with soap and water. Seek medical attention if irritation develops.

Eye contact: Flush eyes with water for at least 15 minutes. If irritation persists, seek medical attention.

Inhalation: Remove to fresh air. If adverse symptoms develop, seek medical attention.

Ingestion: If adverse symptoms develop, seek medical attention.

MATERIAL SAFETY DATA SHEET





MSDS Number: Revision date: Revision number:

V322N 05/24/01 001 Page 2 of 2

Manufacturer: Integra Chemical Co. 710 Thomas Ave SW Renton WA 98055 425.277.9244

24 Hour Emergency Response Telephone: 800-451-8346

REACTIVITY DATA

Stability:

Stable

Hazardous polymerization: Will not occur

Incompatibles:

Incompatible with strong acids, strong bases, strong oxidizers.

Decompostion products:

Oxides of carbon (CO, CO2)

Conditions to avoid:

Exposure to light, air, moisture and high temperatures.

SPILL AND DISPOSAL PROCEDURES

Spill and leak procedures: Sweep or scoop into clean, dry disposal container. Wear protective equipment. Flush spill area with water.

Disposal procedures: Dispose in accordance with all Local, State and Federal regulations.

PROTECTIVE EQUIPMENT

Ventilation: Use adequate general or local exhaust ventilation to keep fume dust levels as low as possible.

Respiratory protection: None needed unless use generates annoying or irritating dusts. Use a dust respirator mask if necessary.

Skin and eye protective equipment: Safety glasses. Use good chemical handling practices.

STORAGE AND HANDLING PRECAUTIONS

Storage area: General.

Store in a cool, dry area. Keep away from incompatible substances. Protect from direct light and minimize contact with air. Protect containers from physical damage. Keep material dry.

TRANSPORTATION INFORMATION

Material is not regulated via either ground or air transportation.

REGULATORY INFORMATION

TSCA Inventory: Yes

CERCLA RQ:

SARA EHS TPQ:

SARA 313 Toxic Release de minimus:

SARA hazard categories: Acute: NO; Chronic: NO; Flammability: NO; Pressure: NO; Reactivity: NO

Clean air act categories: SOCMI: NO; HAP: NO; Volatile HAP: NO; Organic HAP: NO; Ozone depleting: NO

FDA Recommended Dietary Allowance for ascorbic acid: 60mg/day

NSF60 Maximum Use: 12mg/L

MSDS Revision History:

Original MSDS

NE = Not established; NA = Not applicable or Not available

The information presented above is offered for informational purposes only. This MSDS, and the associated product, is intended for use only by technically qualified persons, and at their own discretion and risk. Since conditions and manner of use are outside the control of Integra Chemical Company, we make no warranties, either expressed or implied, and assume no liability in connection with any use of the information.

MATERIAL SAFETY DATA SHEET

Tramfloc, Inc. P. O. Box 350 Tempe, AZ 85280 480-491-6895

> Effective date: 10-30-02 Supersedes: 4-4-00

I. IDENTIFICATION

Product: Calcium Thiosulfate Solution

Chemical Name: Calcium Thiosulfate Solution

Formula: CaS₂O₃

Chemical Family: Inorganic Salt

II. COMPOSITION

Chemical

CAS#

Concentration

Regulation

Calcium Thiosulfate

10124-41-1

30%w/v

No

III. HAZARDOUS IDENTIFICATION

CERCLA Ratings (0-3):

Health = 0 Fire = 0 Reactivity = 0 Persistence = 0

NFPA Ratings (0-4):

Health = 0 Fire = 0 Reactivity = 0

NSF International Standard 60 listed for use in drinking water.

IV. EMERGENCY AND FIRST AID PROCEDURES

POTENTIAL SHORT-TERM HEALTH EFFECTS:

SKIN CONTACT: Immediately flush with large quantities of water, remove contaminated clothing and shoes and wash product from skin.

EYE CONTACT: Immediately flush eyes with clean water, lifting upper and lower lids, for at least 15-20 minutes. Obtain medical attention if irritation occurs or persist.

INGESTION: If vomiting occurs, keep head lower than hips to help prevent aspiration. Treat symptomatically and supportively. Get medical attention if needed.

INHALATION: Remove victim from contaminated area. If breathing is labored, administer oxygen. If breathing has ceased, clear the airway and begin mouth to mouth.

LONG-TERM HEALTH EFFECTS: No information on long-term effects is available.

V. FIRE AND EXPLOSION HAZARD

Negligible hazard when exposed to heat or flame

EXTINGUISHING MEDIA: Extinguish using agent suitable for type of surrounding fire

FIRE FIGHTING: Move container from fire area if possible. Avoid breathing vapors. Keep upwind. Use agents suitable for type of surrounding fire. Avoid breathing hazardous vapors. Keep upwind.

HAZARDOUS COMBUSTION PRODUCTS: Thermal decomposition products may include toxic oxides of sulfur.

FLASH POINT: n/d

FLAMMABLE LIMITS IN AIR: n/d

AUTO IGNITION TEMPERATURE (degrees C (F): n/d

EXTINGUISHING MEDIA: CO₂, dry chemical foam, water spray

VI. ACCIDENTAL RELEASE MEASURES

Absorb small spills with sand, earth, sweeping compound or other inert absorbent. Dispose of in accordance with all government regulations. Large spills should be diked to prevent entry of large quantities of product into sewers or drains. Recover as much of solution as possible. On large spills, land application could be possible as long as application rates are not exceeded, please check with the local Ag Commissioner for permission. Dispose of in accordance with applicable local, county, state, and federal regulations.

VII. HANDLING AND STORAGE

Do not heat drums with any welding equipment as explosion may occur. Avoid breathing gas. Do not get in eyes, on skin, or on clothing. Store in a cool, dry place in properly designed vessels.

VIII. EXPOURE CONTROLS / PERSONAL PROTECTIONS

No occupational exposure limits have been established by OSHA, ACGIH, or NIOSH.

PROTECTIVE EQUIPMENT SHOULD BE USED DURING THE FOLLOWING PROCEDURES:

- Manufacture or formulation of this product
- Repair and maintenance of contaminated equipment.
- Clean up of leaks and spills
- Any other activity that may result in hazardous exposures.

RESPIRATORY PROTECTION:

None generally required. If conditions exist where excessive mist might be generated, a mist respirator is recommended.

In case of emergency conditions such as fire, high heat, and/or contact with acids, use a NIOSH / MSHA approved full-face respirator with SO2 gas cartridge. Use positive

pressure self-contained breathing apparatus for emergency or other conditions requiring a higher level of protection.

CLOTHING: Rubber gloves and apron should be used for prolonged or repeated contact. Safety glasses or chemical goggles are recommended to avoid eye contact. Do not wear contact lenses.

IX. PHYSICAL AND CHEMICAL PROPERTIES

DESCRIPTION: Clear colorless solution

Molecular Weight: 152.20

Water Solubility: Completely soluble in water Molecular formula for active ingredient: CaS₂O₃ Solvent Solubility: Nearly insoluble in alcohol

Specific Gravity: 1.245

pH: 6.5 - 7.5

Vapor pressure: (mm Hg) N/D

X. STABILITY AND REACTIVITY

Stable under normal conditions and pressures.

CONDITIONS TO AVOID: Avoid contact with acids. Sulfur dioxide could be released if mixed with acids.

INCOMPATIBILITIES: Reacts with acid to form sulfur dioxide. Corrosive to brass and copper.

XI. TOXICOLOGICAL INFORMATION:

LD 50 (rat): Anhydrous CaS2O3: 374 mg/kg intravenous

LD 50 (rat): 573 mg/kg intraperitoneal

LD 50 (mouse): rat LD 50; 115 mg/kg intraperitoneal

CARCINOGEN STATUS: None

ACUTE TOXICITY LEVEL: Insufficient data.

TARGET EFFECTS: No data available. **SKIN CONTACT:** May be irritating **EYE CONTACT:** May be irritating.

INGESTION: Thiosulfate salts

Thiosulfate salts are poorly absorbed from the alimentary

tract. Ingestion may result in a cathartic effect.

CHRONIC EXPOSURE: No data available for any type of exposure.

XII. DISPOSAL CONSIDERATIONS

Contaminated cleanup materials may be hazardous. Refer to Sections IV and VIII of this MSDS sheet before handling. All contaminated materials should be placed in disposable containers and buried in an approved dumping area. Follow all local rules governing waste disposal in your area.

XIII. TRANSPORTATION INFORMATION

Classification: Not hazardous by D.O.T. Regulations D.O.T. Proper Shipping Name: Calcium Thiosulfate

Other Requirements: N\A

XIV. REGULATORY INFORMATION

REGULATORY INFORMATION

SARA TITLE III SECTION 313: NOT LISTED RCRA HAZARDOUS WASTE: NOT LISTED CA Prop. 65: NOT LISTED

XV. OTHER INFORMATION

The information contained herein is to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, Tramfloc, Inc. makes no guarantee for results obtained, and assumes no responsibility for damages incurred by use of this product. It is the responsibility of the user to comply with all federal, state and local laws and regulations.

Report Date: 29-Feb-08 09:59



√	Final Report
	Re-Issued Report
	Revised Report

Laboratory Report

Tetra Tech Rizzo One Grant Street - P.O. Box 9005 Framingham, MA 01701

Attn: Dimitri Gounis

Project: 341 Mount Auburn St - Watertown, MA

Project 12701003-003

Laboratory IDClient Sample IDMatrixDate SampledDate ReceivedSA74755-01Crawl SpaceGround Water20-Feb-08 11:0020-Feb-08 17:42

I attest that the information contained within the report has been reviewed for accuracy and checked against the quality control requirements for each method. These results relate only to the sample(s) as received.

All applicable NELAC requirements have been met.

Please note that this report contains 18 pages of analytical data plus Chain of Custody document(s).

This report may not be reproduced, except in full, without written approval from Spectrum Analytical, Inc.

Massachusetts Certification # M-MA138/MA1110

Connecticut # PH-0777 Florida # E87600/E87936 Maine # MA138 New Hampshire # 2538 New Jersey # MA011/MA012 New York # 11393/11840 Rhode Island # 98

USDA # S-51435 Vermont # VT-11393



Authorized by:

Hanibal C. Tayeh, Ph.D. President/Laboratory Director

Technical Reviewer's Initial:



Spectrum Analytical, Inc. is a NELAC accredited laboratory organization and meets NELAC testing standards. Use of the NELAC logo however does not insure that Spectrum is currently accredited for the specific method or analyte indicated. Please refer to our "Quality" web page at www.spectrum-analytical.com for a full listing of our current certifications and fields of accreditation. States in which Spectrum Analytical, Inc. holds NELAC certification are New York, New Hampshire, New Jersey and Florida. All analytical work for Volatile Organic and Air analysis are transferred to and conducted at our 830 Silver Street location (NY-11840, FL-E87936 and NJ-MA012).

Client Project # 12701003-003

<u>Matrix</u> Ground Water Collection Date/Time 20-Feb-08 11:00 Received 20-Feb-08

CAS No.	Analyte(s)	Result	Flag	Units	*RDL	Dilution	Method Ref.	Prepared	Analyzed	Batch	Analys
Volatile O	Organic Compounds										
/olatile C	Organic Compounds by GCMS										
Prepared	by method SW846 5030 Water N	1S									
7-64-1	Acetone	BRL		μg/l	20.0	1	EPA 624	26-Feb-08	26-Feb-08	8021672	EQ
1-43-2	Benzene	BRL		μg/l	1.0	1	n n	u u	"	"	"
5-27-4	Bromodichloromethane	BRL		μg/l	1.0	1	"	"	"	"	"
5-25-2	Bromoform	BRL		μg/l	1.0	1	n n	u u	"	"	"
4-83-9	Bromomethane	BRL		μg/l	2.0	1	n n	u u	"	"	"
8-93-3	2-Butanone (MEK)	BRL		μg/l	10.0	1	n n	u u	"	"	"
6-23-5	Carbon tetrachloride	BRL		μg/l	1.0	1	n n	u u	"	"	"
08-90-7	Chlorobenzene	BRL		μg/l	1.0	1	n n	u u	"	"	"
5-00-3	Chloroethane	BRL		μg/l	2.0	1	n n	u u	"	"	"
7-66-3	Chloroform	BRL		μg/l	1.0	1	"	"	"	"	"
4-87-3	Chloromethane	BRL		μg/l	2.0	1	"	"	"	"	"
24-48-1	Dibromochloromethane	BRL		μg/l	1.0	1	"	"	"	"	"
5-50-1	1,2-Dichlorobenzene	BRL		μg/l	1.0	1	"	"	"	"	"
41-73-1	1,3-Dichlorobenzene	BRL		μg/l	1.0	1	"	"	"	"	"
06-46-7	1,4-Dichlorobenzene	BRL		μg/l	1.0	1	"	"	"	"	"
5-34-3	1,1-Dichloroethane	BRL		μg/l	1.0	1	"	"	"	"	"
07-06-2	1,2-Dichloroethane	BRL		μg/l	1.0	1	"	"	"	"	"
5-35-4	1,1-Dichloroethene	BRL		μg/l	1.0	1	"	"	"	"	"
56-59-2	cis-1,2-Dichloroethene	BRL		μg/l	1.0	1	"	"	"	"	"
56-60-5	trans-1,2-Dichloroethene	BRL		μg/l	1.0	1	"	"	"	"	"
8-87-5	1,2-Dichloropropane	BRL		μg/l	1.0	1	"	"	"	"	"
0061-01-5	cis-1,3-Dichloropropene	BRL		μg/l	1.0	1	"	"	"	"	"
	trans-1,3-Dichloropropene	BRL		μg/l	1.0	1	"	"	"	"	"
00-41-4	Ethylbenzene	BRL		μg/l	1.0	1	п	··	"	"	"
91-78-6	2-Hexanone (MBK)	BRL		μg/l	10.0	1	п	"	"	"	"
634-04-4	Methyl tert-butyl ether	BRL		μg/l	1.0	1	п	u	"	"	"
08-10-1	4-Methyl-2-pentanone (MIBK)	BRL		μg/l	10.0	1	п	u	"	"	"
5-09-2	Methylene chloride	BRL		μg/l	10.0	1	п	u u	"	"	"
00-42-5	Styrene	BRL		μg/l	1.0	1	n n	"	"	"	"
9-34-5	1,1,2,2-Tetrachloroethane	BRL		μg/l	1.0	1	n n	"	"	"	"
27-18-4	Tetrachloroethene	BRL		μg/l	1.0	1	"	"	"	"	"
08-88-3	Toluene	BRL		μg/l	1.0	1	"	"	"	"	"
1-55-6	1,1,1-Trichloroethane	BRL		μg/l	1.0	1	"	"	"	"	"
9-00-5	1,1,2-Trichloroethane	BRL		μg/l	1.0	1	"	"	"	"	"
9-01-6	Trichloroethene	BRL		μg/l	1.0	1	"	"	"	"	"
5-69-4	Trichlorofluoromethane (Freon 11)	BRL		μg/l	1.0	1	"	"	"	"	"
5-01-4	Vinyl chloride	BRL		μg/l	1.0	1	"	u u	"	"	"
330-20-7	m,p-Xylene	BRL		μg/l	2.0	1	"	"	"	"	"
5-47-6	o-Xylene	BRL		μg/l	1.0	1	"	"	"	"	"
Surrogato	recoveries:			*							
160-00-4	4-Bromofluorobenzene	105		70-13	30 %		"	"	"	"	"
037-26-5	Toluene-d8	99		70-13			"	"	"	"	
	1,2-Dichloroethane-d4	99		70-13 70-13			"		"		
	Dibromofluoromethane	97		70-13			"		"		
	ractable Organic Compounds	31		70-13	.5 /0						
	•										
	actables by EPA 504.1										
	by method SW846 3510C	551			0.0:		ED4 :	07.5	00 5 : 1 -	0001===	
6-12-8	1,2-Dibromo-3-chloropropane	BRL		μg/l 	0.0100	1	EPA 504.1	27-Feb-08	28-Feb-08		SM
06-93-4	1,2-Dibromoethane (EDB)	BRL		μg/l	0.0100	1	"	"			"

Client Project # 12701003-003

<u>Matrix</u> Ground Water Collection Date/Time 20-Feb-08 11:00 Received 20-Feb-08

CAS No.	Analyte(s)	Result	Flag	Units	*RDL	Dilution	Method Ref.	Prepared	Analyzed	Batch	Analys
Semivolat	tile Organic Compounds by GCM	18									
PAHs by	SW846 8270C										
Prepared	by method SW846 3510C										
33-32-9	Acenaphthene	BRL		μg/l	2.78	1	SW846 8270C	25-Feb-08	27-Feb-08	8021521	M.B
208-96-8	Acenaphthylene	BRL		μg/l	2.78	1	"	"	"	"	"
20-12-7	Anthracene	BRL		μg/l	2.78	1	"	"	"	"	"
6-55-3	Benzo (a) anthracene	BRL		μg/l	2.78	1	"	"	"	"	"
0-32-8	Benzo (a) pyrene	BRL		μg/l	2.78	1	"	"	"	"	"
05-99-2	Benzo (b) fluoranthene	BRL		μg/l	2.78	1	"	"	"	"	"
91-24-2	Benzo (g,h,i) perylene	BRL		μg/l	2.78	1	"	u u	"	"	"
07-08-9	Benzo (k) fluoranthene	BRL		μg/l	2.78	1	"	u u	"	"	"
18-01-9	Chrysene	BRL		μg/l	2.78	1	"	u u	"	"	"
3-70-3	Dibenzo (a,h) anthracene	BRL		μg/l	2.78	1	"	"	"	"	"
06-44-0	Fluoranthene	BRL		μg/l	2.78	1	"	u u	"	"	"
6-73-7	Fluorene	BRL		μg/l	2.78	1	"	"	"	"	"
93-39-5	Indeno (1,2,3-cd) pyrene	BRL		μg/l	2.78	1	"	"	"	"	"
0-12-0	1-Methylnaphthalene	BRL		μg/l	2.78	1	"	"	"	"	"
1-57-6	2-Methylnaphthalene	BRL		μg/l	2.78	1	"	"	"	"	"
1-20-3	Naphthalene	BRL		μg/l	2.78	1	"	"	"	"	"
5-01-8	Phenanthrene	BRL		μg/l	2.78	1	"	"	"	"	"
29-00-0	Pyrene	BRL		μg/l	2.78	1	"	"	"	"	"
Surrogate	recoveries:										
21-60-8	2-Fluorobiphenyl	55		30-13	30 %		"	u u	"	"	"
718-51-0	Terphenyl-dl4	56		30-13	30 %		"	"	"	"	
	actables/Phenols by SW846 82	270C									
	by method SW846 3510C										
9-50-7	4-Chloro-3-methylphenol	BRL		μg/l	2.78	1	"	"	"	"	"
5-57-8	2-Chlorophenol	BRL		μg/l	2.78	1	"	"	"	"	
20-83-2	2,4-Dichlorophenol	BRL		μg/l	2.78	1	"	"	"		
05-67-9	2,4-Dimethylphenol	BRL		μg/l	2.78	1			"		
34-52-1	4,6-Dinitro-2-methylphenol	BRL		μg/l	2.78	1			"		"
1-28-5	2,4-Dinitrophenol	BRL		μg/l	2.78	1	"	"	"		
5-48-7	2-Methylphenol	BRL		μg/l	2.78	1			"		
08-39-4,	3,4-Methylphenol	BRL		μg/l	5.56	1	"	"	"	"	
06-44-5	5,4-Methylphenol			P3'	0.00	•					
8-75-5	2-Nitrophenol	BRL		μg/l	2.78	1	"	"	"	"	"
00-02-7	4-Nitrophenol	BRL		μg/l	2.78	1	"	"	"	"	"
7-86-5	Pentachlorophenol	BRL		μg/l	2.78	1	u u	"	"	"	"
08-95-2	Phenol	BRL		μg/l	2.78	1	u u	"	"	"	"
5-95-4	2,4,5-Trichlorophenol	BRL		μg/l	2.78	1	u u	"	"	"	"
8-06-2	2,4,6-Trichlorophenol	BRL		μg/l	2.78	1	"	"	"	"	"
Surrogate	recoveries:										
367-12-4	2-Fluorophenol	51		15-11	10 %		"	"	"	"	"
165-62-2	Phenol-d5	40		15-11	10 %		"	"	"	"	"
emivolat	tile Organic Compounds by GC										
	rinated Biphenyls by EPA 608										
•	by method SW846 3510C										
	Aroclor-1016	BRL		μg/l	0.211	1	EPA 608	25-Feh-08	26-Feb-08	8021525	IMR
2674.11 2		BRL		μg/l	0.211	1	LFA 000	23-1 C D-00	"	"	IIVIIN
	ALOCIOI-1771	DIXL				1	"	"	_		
1104-28-2		PDI		110/					"		
1104-28-2 1141-16-5	Aroclor-1232	BRL		μg/l	0.211				"	"	
1104-28-2 1141-16-5 3469-21-9		BRL BRL BRL		µg/l µg/l µg/l	0.211 0.211 0.211	1	"		"		

Sample Identification Crawl Space SA74755-01

Client Project # 12701003-003

<u>Matrix</u> Ground Water Collection Date/Time 20-Feb-08 11:00 Received 20-Feb-08

CAS No.	Analyte(s)	Result	Flag	Units	*RDL	Dilution	Method Ref.	Prepared	Analyzed	Batch	Analyst
Semivolati	ile Organic Compounds by GC										
Polychlori	inated Biphenyls by EPA 608										
Prepared	by method SW846 3510C										
	Aroclor-1260	BRL		μg/l	0.211	1	EPA 608	25-Feb-08	26-Feb-08	8021525	IMR
	Aroclor-1262	BRL		μg/l	0.211	1	u u	"	"	"	"
	Aroclor-1268	BRL		μg/l	0.211	1	u	"	"	"	"
Surrogate i	recoveries:										
2051-24-3	Decachlorobiphenyl (Sr)	66		30-1	50 %		u u	u	"	"	"
10386-84-2	4,4-DB-Octafluorobiphenyl (Sr)	64		30-1	50 %		II .	"	"	"	"
Extractab	le Petroleum Hydrocarbons										
	Non-polar material (SGT-HEM)	BRL		mg/l	1.0	1	EPA 1664 Rev. A	22-Feb-08	24-Feb-08	8021419	JK
Total Met	als by EPA 200 Series Methods										
7440-22-4	Silver	BRL		mg/l	0.0050	1	EPA 200.7	22-Feb-08	25-Feb-08	8021350	SA/
7440-38-2	Arsenic	BRL		mg/l	0.0040	1	II .	u	"	"	"
7440-43-9	Cadmium	BRL		mg/l	0.0025	1	II .	u	"	"	"
7440-47-3	Chromium	BRL		mg/l	0.0080	1	II .	u	"	"	"
7439-89-6	Iron	BRL		mg/l	0.0550	1	W	"	"	"	"
General C	hemistry Parameters										
1854-029-9	Hexavalent Chromium	BRL		mg/l	0.008	1	SW846 7196A/SM3500CrD	20-Feb-08 19:18	20-Feb-08	8021303	CKA
57-12-5	Cyanide (total)	BRL		mg/l	0.0100	1	10-204-00-1-A / SW846 9012A / EPA 335.4	21-Feb-08	22-Feb-08	8021402	eem
7782-50-5	Total Residual Chlorine	0.045		mg/l	0.020	1	Hach 8167	20-Feb-08 19:35	20-Feb-08	8021304	CKA
	Total Suspended Solids	5.00		mg/l	5.00	1	SM2540D	21-Feb-08	21-Feb-08	8021348	DN

A 1770	D 4	FI	TT '4	*DDI	Spike	Source	0/DEC	%REC	nnn	RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021672 - SW846 5030 Water MS										
Blank (8021672-BLK1)										
Prepared & Analyzed: 26-Feb-08										
Acetone	BRL		μg/l	20.0						
Benzene	BRL		μg/l	1.0						
Bromodichloromethane	BRL		μg/l	1.0						
Bromoform	BRL		μg/l	1.0						
Bromomethane	BRL		μg/l	2.0						
2-Butanone (MEK)	BRL		μg/l	10.0						
Carbon tetrachloride	BRL		μg/l	1.0						
Chlorobenzene	BRL		μg/l	1.0						
Chloroethane	BRL		μg/l	2.0						
Chloroform	BRL		μg/l	1.0						
Chloromethane	BRL		μg/l	2.0						
Dibromochloromethane	BRL		μg/l	1.0						
1,2-Dichlorobenzene	BRL		μg/l	1.0						
1,3-Dichlorobenzene	BRL		μg/l	1.0						
1,4-Dichlorobenzene	BRL		μg/l	1.0						
1,1-Dichloroethane	BRL		μg/l	1.0						
1,2-Dichloroethane	BRL		μg/l	1.0						
1,1-Dichloroethene	BRL		μg/l	1.0						
cis-1,2-Dichloroethene	BRL		μg/l	1.0						
trans-1,2-Dichloroethene	BRL		μg/l	1.0						
1,2-Dichloropropane	BRL		μg/l	1.0						
cis-1,3-Dichloropropene	BRL		μg/l	1.0						
trans-1,3-Dichloropropene	BRL		μg/l	1.0						
Ethylbenzene	BRL		μg/l	1.0						
2-Hexanone (MBK)	BRL		μg/l	10.0						
Methyl tert-butyl ether	BRL		μg/l	1.0						
4-Methyl-2-pentanone (MIBK)	BRL		μg/l	10.0						
Methylene chloride	BRL		μg/l	10.0						
Styrene	BRL		μg/l	1.0						
1,1,2,2-Tetrachloroethane	BRL		μg/l	1.0						
Tetrachloroethene	BRL		μg/l	1.0						
Toluene	BRL		μg/l	1.0						
1,1,1-Trichloroethane	BRL		μg/l	1.0						
1,1,2-Trichloroethane	BRL		μg/l	1.0						
Trichloroethene	BRL		μg/l	1.0						
Trichlorofluoromethane (Freon 11)	BRL		μg/l	1.0						
Vinyl chloride	BRL		μg/l	1.0						
m,p-Xylene	BRL		μg/l	2.0						
o-Xylene	BRL		μg/l	1.0						
Surrogate: 4-Bromofluorobenzene	31.8		μg/l	***	30.0		106	70-130		
Surrogate: Toluene-d8	28.9		μg/l		30.0		96	70-130		
Surrogate: 1,2-Dichloroethane-d4	28.2		μg/l		30.0		94	70-130		
Surrogate: Dibromofluoromethane	29.0		μg/l		30.0		97	70-130		
LCS (8021672-BS1)										
Prepared & Analyzed: 26-Feb-08										
Acetone	13.9		μg/l		20.0		70	70-130		
Benzene	20.1		μg/l		20.0		101	70-130		
Bromodichloromethane	19.3		μg/l		20.0		96	35-155		
Bromoform	18.8		μg/l		20.0		94	45-169		
Bromomethane	20.1		μg/l		20.0		101	1-242		

Analyte(s)	Result	Flag	Units	*RDL	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit
Batch 8021672 - SW846 5030 Water MS										
LCS (8021672-BS1)										
Prepared & Analyzed: 26-Feb-08										
2-Butanone (MEK)	15.5		μg/l		20.0		78	70-130		
Carbon tetrachloride	17.7		μg/l		20.0		88	70-140		
Chlorobenzene	21.9		μg/l		20.0		109	70-130		
Chloroethane	20.0		μg/l		20.0		100	14-230		
Chloroform	18.2		μg/l		20.0		91	51-138		
Chloromethane	22.9		μg/l		20.0		114	1-273		
Dibromochloromethane	19.0		μg/l		20.0		95	53-149		
1,2-Dichlorobenzene	20.2		μg/l		20.0		101	18-190		
1,3-Dichlorobenzene	22.8		μg/l		20.0		114	59-156		
1,4-Dichlorobenzene	19.7				20.0		99	18-190		
1,1-Dichloroethane	19.7		µg/l		20.0		96	59-155		
1,2-Dichloroethane	16.4		µg/l		20.0		96 82	49-155		
1,1-Dichloroethane	18.0		µg/l		20.0		90	70-130		
			µg/l		20.0		90 97	70-130 70-130		
cis-1,2-Dichloroethene	19.4		µg/l		20.0					
trans-1,2-Dichloroethene	18.3		μg/l				92	54-156		
1,2-Dichloropropane	18.6		μg/l		20.0		93	1-210		
cis-1,3-Dichloropropene	18.6		μg/l "		20.0		93	1-227		
trans-1,3-Dichloropropene	18.8		μg/l "		20.0		94	17-183		
Ethylbenzene	23.3		μg/l 		20.0		116	37-162		
2-Hexanone (MBK)	16.1		μg/l 		20.0		81	70-130		
Methyl tert-butyl ether	16.1		μg/l		20.0		80	70-130		
4-Methyl-2-pentanone (MIBK)	15.4		μg/l		20.0		77	70-130		
Methylene chloride	18.8		μg/l		20.0		94	1-221		
Styrene	22.9		μg/l		20.0		114	70-130		
1,1,2,2-Tetrachloroethane	16.4		μg/l		20.0		82	46-157		
Tetrachloroethene	21.9		μg/l		20.0		109	64-148		
Toluene	20.6		μg/l		20.0		103	70-130		
1,1,1-Trichloroethane	18.7		μg/l		20.0		94	52-162		
1,1,2-Trichloroethane	18.4		μg/l		20.0		92	52-150		
Trichloroethene	20.3		μg/l		20.0		102	71-157		
Trichlorofluoromethane (Freon 11)	17.7		μg/l		20.0		88	17-181		
Vinyl chloride	23.4		μg/l		20.0		117	1-251		
m,p-Xylene	46.6		μg/l		40.0		116	70-130		
o-Xylene	23.0		μg/l		20.0		115	70-130		
Surrogate: 4-Bromofluorobenzene	31.0		μg/l		30.0		103	70-130		
Surrogate: Toluene-d8	30.4		μg/l		30.0		101	70-130		
Surrogate: 1,2-Dichloroethane-d4 Surrogate: Dibromofluoromethane	25.7 27.8		μg/l μg/l		30.0 30.0		86 93	70-130 70-130		
LCS Dup (8021672-BSD1)	27.0		μул		50.0		30	70 700		
Prepared & Analyzed: 26-Feb-08										
Acetone	13.6	QC1	μg/l		20.0		68	70-130	2	30
Benzene	19.2		μg/l		20.0		96	70-130	5	30
Bromodichloromethane	18.9		μg/l		20.0		95	35-155	2	30
Bromoform	20.8		μg/l		20.0		104	45-169	10	30
Bromomethane	17.7		μg/l		20.0		88	1-242	13	30
2-Butanone (MEK)	14.6		μg/l		20.0		73	70-130	6	30
Carbon tetrachloride	18.5				20.0		93	70-130	5	30
Chlorobenzene	21.0		µg/l		20.0		93 105	70-140 70-130	4	30
			µg/l							
Chloroform	16.5		μg/l		20.0		83	14-230	19	30
Chloroform	18.9		μg/l		20.0		95	51-138	4	30

Analyte(s)	Result	Flag	Units	*RDL	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit
Batch 8021672 - SW846 5030 Water	r MS									
LCS Dup (8021672-BSD1)										
Prepared & Analyzed: 26-Feb-08										
Chloromethane	16.1	QR2	μg/l		20.0		80	1-273	35	30
Dibromochloromethane	16.8		μg/l		20.0		84	53-149	12	30
1,2-Dichlorobenzene	19.2		μg/l		20.0		96	18-190	5	30
1,3-Dichlorobenzene	21.0		μg/l		20.0		105	59-156	8	30
1,4-Dichlorobenzene	19.0		μg/l		20.0		95	18-190	4	30
1,1-Dichloroethane	19.4		μg/l		20.0		97	59-155	1	30
1,2-Dichloroethane	16.9		μg/l		20.0		84	49-155	3	30
1,1-Dichloroethene	19.0		μg/l		20.0		95	70-130	5	30
cis-1,2-Dichloroethene	20.1		μg/l		20.0		100	70-130	4	30
trans-1,2-Dichloroethene	19.0		μg/l		20.0		95	54-156	4	30
1,2-Dichloropropane	18.2		μg/l		20.0		91	1-210	2	30
cis-1,3-Dichloropropene	17.7		μg/l		20.0		89	1-227	5	30
trans-1,3-Dichloropropene	17.4		μg/l		20.0		87	17-183	8	30
Ethylbenzene	22.0		μg/l		20.0		110	37-162	6	30
2-Hexanone (MBK)	15.3		μg/l		20.0		76	70-130	5	30
Methyl tert-butyl ether	17.6		μg/l		20.0		88	70-130	9	30
4-Methyl-2-pentanone (MIBK)	15.4		μg/l		20.0		77	70-130	0.1	30
Methylene chloride	18.2		μg/l		20.0		91	1-221	3	30
Styrene	22.0		μg/l		20.0		110	70-130	4	30
1,1,2,2-Tetrachloroethane	17.1		μg/l		20.0		85	46-157	4	30
Tetrachloroethene	19.4		μg/l		20.0		97	64-148	12	30
Toluene	19.1		μg/l		20.0		95	70-130	8	30
1,1,1-Trichloroethane	19.8		μg/l		20.0		99	52-162	6	30
1,1,2-Trichloroethane	17.6		μg/l		20.0		88	52-150	5	30
Trichloroethene	19.4		μg/l		20.0		97	71-157	5	30
Trichlorofluoromethane (Freon 11)	19.7		μg/l		20.0		99	17-181	11	30
Vinyl chloride	19.6		μg/l		20.0		98	1-251	18	30
m,p-Xylene	44.6		μg/l		40.0		111	70-130	4	30
o-Xylene	22.2		μg/l		20.0		111	70-130	4	30
Surrogate: 4-Bromofluorobenzene	32.8		μg/l		30.0		109	70-130		
Surrogate: Toluene-d8	29.0		μg/l		30.0		97	70-130		
Surrogate: 1,2-Dichloroethane-d4 Surrogate: Dibromofluoromethane	27.4 28.4		μg/l		30.0 30.0		91 95	70-130 70-130		
· ·			μg/l		30.0		90	70-130		
	Source: SA74755-01									
Prepared & Analyzed: 26-Feb-08			_							
Benzene	22.8		μg/l 		20.0	BRL	114	70-130		
Bromodichloromethane	21.6		μg/l		20.0	BRL	108	35-155		
Bromoform	21.4		μg/l		20.0	BRL	107	45-169		
Bromomethane	22.4		μg/l		20.0	BRL	112	1-242		
Carbon tetrachloride	24.0		μg/l		20.0	BRL	120	70-140		
Chlorobenzene	24.1		μg/l		20.0	BRL	120	70-130		
Chloroethane	21.0		µg/l		20.0	BRL	105	14-230		
Chloroform	22.6		μg/l		20.0	BRL	113	51-138		
Chloromethane	21.4		μg/l		20.0	BRL	107	1-273		
Dibromochloromethane	20.3		μg/l		20.0	BRL	102	53-149		
1,2-Dichlorobenzene	22.6		μg/l "		20.0	BRL	113	18-190		
1,3-Dichlorobenzene	24.2		μg/l "		20.0	BRL	121	59-156		
1,4-Dichlorobenzene	22.5		μg/l 		20.0	BRL	112	18-190		
1,1-Dichloroethane	22.7		μg/l		20.0	BRL	113	59-155		
1,2-Dichloroethane	20.1		μg/l		20.0	BRL	100	49-155		

Analyte(s)	Result	Flag Units	*RDL	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit
		riag Ollits	KDL	Level	Result	/0KEC	Lillius	KI D	Lillit
Batch 8021672 - SW846 5030 Wa	ter MS								
Matrix Spike (8021672-MS1)	Source: SA74755-01								
Prepared & Analyzed: 26-Feb-08									
1,1-Dichloroethene	23.2	μg/l		20.0	BRL	116	70-130		
trans-1,2-Dichloroethene	23.0	μg/l		20.0	BRL	115	54-156		
1,2-Dichloropropane	20.9	μg/l		20.0	BRL	104	1-210		
cis-1,3-Dichloropropene	20.5	μg/l		20.0	BRL	103	1-227		
trans-1,3-Dichloropropene	19.8	μg/l		20.0	BRL	99	17-183		
Ethylbenzene	25.6	μg/l		20.0	BRL	128	37-162		
Methylene chloride	20.5	μg/l		20.0	BRL	103	1-221		
1,1,2,2-Tetrachloroethane	18.2	μg/l		20.0	BRL	91	46-157		
Tetrachloroethene	24.5	μg/l		20.0	BRL	122	64-148		
Toluene	22.3	μg/l		20.0	BRL	112	70-130		
1,1,1-Trichloroethane	23.9	μg/l		20.0	BRL	120	52-162		
1,1,2-Trichloroethane	19.8	μg/l		20.0	BRL	99	52-150		
Trichloroethene	23.3	μg/l		20.0	BRL	116	71-157		
Trichlorofluoromethane (Freon 11)	25.1	μg/l		20.0	BRL	125	17-181		
Vinyl chloride	26.0	μg/l		20.0	BRL	130	1-251		
Surrogate: 4-Bromofluorobenzene	32.4	μg/l		30.0		108	70-130		
Surrogate: Toluene-d8	30.0	μg/l		30.0		100	70-130		
Surrogate: 1,2-Dichloroethane-d4 Surrogate: Dibromofluoromethane	28.9 29.1	μg/l μg/l		30.0 30.0		96 97	70-130 70-130		
Matrix Spike Dup (8021672-MSD1)		F-3· ·							
Prepared & Analyzed: 26-Feb-08	Source. SAT-1755-01								
Benzene	23.8	μg/l		20.0	BRL	119	70-130	4	30
Bromodichloromethane	22.6	μg/l		20.0	BRL	113	35-155	4	30
Bromoform	21.7	μg/l		20.0	BRL	108	45-169	1	30
Bromomethane	24.0	μg/l		20.0	BRL	120	1-242	7	30
Carbon tetrachloride	25.3	μg/l		20.0	BRL	126	70-140	5	30
Chlorobenzene	23.5	μg/l		20.0	BRL	117	70-130	3	30
Chloroethane	23.2	μg/l		20.0	BRL	116	14-230	10	30
Chloroform	23.3	μg/l		20.0	BRL	117	51-138	3	30
Chloromethane	24.8	μg/l		20.0	BRL	124	1-273	15	30
Dibromochloromethane 1.2 Dichlorobenzene	21.6 21.9	μg/l		20.0 20.0	BRL BRL	108 109	53-149 18-190	6 3	30 30
1,2-Dichlorobenzene 1,3-Dichlorobenzene	21.9	μg/l		20.0	BRL	122	59-156	3 0.7	30
1,4-Dichlorobenzene	24.3	μg/l		20.0	BRL	106	18-190	6	30
1,1-Dichloroethane	23.5	μg/l		20.0	BRL	117	59-155	3	30
		μg/l							
1,2-Dichloroethane	20.8	μg/l		20.0	BRL BRL	104	49-155 70-130	4	30 30
1,1-Dichloroethene	24.9	µg/l		20.0		124		7	
trans-1,2-Dichloroethene	23.4	μg/l		20.0	BRL	117	54-156	2	30
1,2-Dichloropropane	21.4	μg/l		20.0	BRL	107	1-210	3	30
cis-1,3-Dichloropropene	21.2	μg/l		20.0	BRL	106 106	1-227	3	30
trans-1,3-Dichloropropene	21.2	μg/l		20.0	BRL	106	17-183	7	30
Ethylbenzene Methylana ablarida	24.5	μg/l		20.0	BRL	123	37-162	4	30
Methylene chloride	22.2	μg/l		20.0	BRL	111	1-221	8	30
1,1,2,2-Tetrachloroethane	19.0	μg/l		20.0	BRL	95 427	46-157	4	30
Tetrachloroethene	25.5	μg/l		20.0	BRL	127	64-148	4	30
Toluene	23.3	μg/l		20.0	BRL	116	70-130	4	30
1,1,1-Trichloroethane	24.8	μg/l		20.0	BRL	124	52-162	4	30
1,1,2-Trichloroethane	21.0	μg/l		20.0	BRL	105	52-150	6	30
Trichloroethene	24.1	μg/l		20.0	BRL	120	71-157	3	30
Trichlorofluoromethane (Freon 11)	26.5	μg/l		20.0	BRL	133	17-181	6	30

					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limi
Batch 8021672 - SW846 5030 Water	r MS									
Matrix Spike Dup (8021672-MSD1)	Source: SA74755-01									
Prepared & Analyzed: 26-Feb-08										
Vinyl chloride	27.9		μg/l		20.0	BRL	140	1-251	7	30
Surrogate: 4-Bromofluorobenzene	32.6		μg/l		30.0		109	70-130		
Surrogate: Toluene-d8	30.8		μg/l		30.0		103	70-130		
Surrogate: 1,2-Dichloroethane-d4	31.5		μg/l		30.0		105	70-130		
Surrogate: Dibromofluoromethane	30.9		μg/l		30.0		103	70-130		
	Microext	ractabl	e Organic	Compound	ls - Quality	y Control				
					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limi
Batch 8021727 - SW846 3510C										
Blank (8021727-BLK1)										
Prepared: 27-Feb-08 Analyzed: 28-Fe	eb-08									
1,2-Dibromo-3-chloropropane	BRL		μg/l	0.0100						
1,2-Dibromoethane (EDB)	BRL		μg/l	0.0100						
LCS (8021727-BS1)										
Prepared: 27-Feb-08 Analyzed: 28-Fe	eb-08									
1,2-Dibromoethane (EDB)	0.250		μg/l	0.0100	0.200		125	50-150		
	2.242			0.0100	0.200		120	50-150		
1,2-Dibromo-3-chloropropane	0.240		µg/l	0.0100	0.200					
	0.240 Source: SA74725-01		μg/ι	0.0100	0.200					
	Source: SA74725-01		μдл	0.0100	0.200					
Duplicate (8021727-DUP1)	Source: SA74725-01		μg/l	0.0100	0.200	BRL				30

Semivolatile Organic Compounds by GCMS - Quality Control

Analyte(s)	Result	Flag	Units	*RDL	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit
Batch 8021521 - SW846 3510C										
Blank (8021521-BLK1)										
Prepared: 25-Feb-08 Analyzed: 27-Feb-08										
Acenaphthene	BRL		μg/l	2.50						
Acenaphthylene	BRL		μg/l	2.50						
Anthracene	BRL		μg/l	2.50						
Benzo (a) anthracene	BRL		μg/l	2.50						
Benzo (a) pyrene	BRL		μg/l	2.50						
Benzo (b) fluoranthene	BRL		μg/l	2.50						
Benzo (g,h,i) perylene	BRL		μg/l	2.50						
Benzo (k) fluoranthene	BRL		μg/l	2.50						
4-Chloro-3-methylphenol	BRL		μg/l	2.50						
2-Chlorophenol	BRL		μg/l	2.50						
Chrysene	BRL		μg/l	2.50						
Dibenzo (a,h) anthracene	BRL		μg/l	2.50						
2,4-Dichlorophenol	BRL		μg/l	2.50						
2,4-Dimethylphenol	BRL		μg/l	2.50						
4,6-Dinitro-2-methylphenol	BRL		μg/l	2.50						
2,4-Dinitrophenol	BRL		μg/l	2.50						
Fluoranthene	BRL		μg/l	2.50						
Fluorene	BRL		μg/l	2.50						
Indeno (1,2,3-cd) pyrene	BRL		μg/l	2.50						
1-Methylnaphthalene	BRL		μg/l	2.50						
2-Methylnaphthalene	BRL		μg/l	2.50						
2-Methylphenol	BRL		μg/l	2.50						
3,4-Methylphenol	BRL		μg/l	5.00						
Naphthalene	BRL		μg/l	2.50						
2-Nitrophenol	BRL		μg/l	2.50						
4-Nitrophenol	BRL		μg/l	2.50						
Pentachlorophenol	BRL		μg/l	2.50						
Phenanthrene	BRL		μg/l	2.50						
Phenol	BRL		μg/l	2.50						
Pyrene	BRL		μg/l	2.50						
2,4,5-Trichlorophenol	BRL		μg/l	2.50						
2,4,6-Trichlorophenol	BRL		μg/l	2.50						
Surrogate: 2-Fluorobiphenyl	34.3		μg/l		50.0		69	30-130		
Surrogate: 2-Fluorophenol Surrogate: Phenol-d5	33.3 25.1		μg/l μg/l		50.0 50.0		67 50	15-110 15-110		
Surrogate: Terphenyl-dl4	31.8		μg/l		50.0		64	30-130		
. ,			13							
LCS (8021521-BS1) Prepared: 25-Feb-08 Analyzed: 27-Feb-08										
•	41.5		ua/l	2.50	50.0		83	40-140		
Acenaphthulana	39.0		μg/l		50.0					
Acenaphthylene Anthracene	38.8		µg/l	2.50 2.50	50.0		78 78	40-140 40-140		
Benzo (a) anthracene	38.8 42.1		µg/l	2.50	50.0		78 84	40-140		
Benzo (a) antinracene Benzo (a) pyrene	42.1 42.1		μg/l μg/l	2.50	50.0		84 84	40-140		
Benzo (b) fluoranthene	46.2			2.50	50.0		92	40-140		
	46.2 42.0		µg/l	2.50 2.50	50.0 50.0		92 84	40-140 40-140		
Benzo (k) fluoranthene			µg/l		50.0					
Benzo (k) fluoranthene	32.4		μg/l	2.50			65 83	40-140		
4-Chloro-3-methylphenol	41.2		μg/l	2.50	50.0		82 77	30-130		
2-Chlorophenol	38.7		μg/l	2.50	50.0		77	30-130		
Chrysene	40.5		μg/l	2.50	50.0		81	40-140		
Dibenzo (a,h) anthracene	41.7		μg/l	2.50	50.0		83	40-140		

Semivolatile Organic Compounds by GCMS - Quality Control

					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limi
Batch 8021521 - SW846 3510C										
_CS (8021521-BS1)										
Prepared: 25-Feb-08 Analyzed: 27-Feb-08										
2,4-Dichlorophenol	41.1		μg/l	2.50	50.0		82	30-130		
2,4-Dimethylphenol	37.6		μg/l	2.50	50.0		75	30-130		
4,6-Dinitro-2-methylphenol	48.1		μg/l	2.50	50.0		96	30-130		
2,4-Dinitrophenol	42.8		μg/l	2.50	50.0		86	30-130		
Fluoranthene	43.6		μg/l	2.50	50.0		87	40-140		
Fluorene	39.2		μg/l	2.50	50.0		78	40-140		
Indeno (1,2,3-cd) pyrene	42.0		μg/l	2.50	50.0		84	40-140		
1-Methylnaphthalene	40.2		μg/l	2.50	50.0		80	40-140		
2-Methylnaphthalene	39.7		μg/l	2.50	50.0		79	40-140		
2-Methylphenol	39.8		μg/l	2.50	50.0		80	30-130		
3,4-Methylphenol	42.4		μg/l	5.00	50.0		85	40-130		
Naphthalene	37.2		μg/l	2.50	50.0		74	40-140		
2-Nitrophenol	40.3		μg/l	2.50	50.0		81	30-130		
4-Nitrophenol	33.3		μg/l	2.50	50.0		67	30-130		
Pentachlorophenol	52.1		μg/l	2.50	50.0		104	30-130		
Phenanthrene	45.0		μg/l	2.50	50.0		90	40-140		
Phenol	39.9		μg/l	2.50	50.0		80	30-130		
Pyrene	40.7		μg/l	2.50	50.0		81	40-140		
2,4,5-Trichlorophenol	41.0		μg/l	2.50	50.0		82	30-130		
2,4,6-Trichlorophenol	41.4		μg/l	2.50	50.0		83	30-130		
Surrogate: 2-Fluorobiphenyl	21.4		μg/l		50.0		43	30-130		
Surrogate: 2-Fluorophenol	20.4		μg/l		50.0		41	15-110		
Surrogate: Phenol-d5 Surrogate: Terphenyl-dl4	15.5 23.1		μg/l μg/l		50.0 50.0		31 46	15-110 30-130		

Semivolatile Organic Compounds by GC - Quality Control

A 1.77	D 1	TO.	** **	*DDI	Spike	Source	A/DEC	%REC	D DD	RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021525 - SW846 3510C										
Blank (8021525-BLK1)										
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Aroclor-1016	BRL		μg/l	0.200						
Aroclor-1016 [2C]	BRL		μg/l	0.200						
Aroclor-1221	BRL		μg/l	0.200						
Aroclor-1221 [2C]	BRL		μg/l	0.200						
Aroclor-1232	BRL		μg/l	0.200						
Aroclor-1232 [2C]	BRL		μg/l	0.200						
Aroclor-1242	BRL		μg/l	0.200						
Aroclor-1242 [2C]	BRL		μg/l	0.200						
Aroclor-1248	BRL		μg/l	0.200						
Aroclor-1248 [2C]	BRL		μg/l	0.200						
Aroclor-1254	BRL		μg/l	0.200						
Aroclor-1254 [2C]	BRL		μg/l	0.200						
Aroclor-1260	BRL		μg/l	0.200						
Aroclor-1260 [2C]	BRL		μg/l	0.200						
Aroclor-1262	BRL		μg/l	0.200						
Aroclor-1262 [2C]	BRL		μg/l	0.200						
Aroclor-1268	BRL		μg/l	0.200						
Aroclor-1268 [2C]	BRL		μg/l	0.200						
Surrogate: Decachlorobiphenyl (Sr)	0.134		µg/l		0.200		67	30-150		
Surrogate: Decachlorobiphenyl (Sr) [2C]	0.142		μg/l		0.200		71	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr)	0.134		μg/l		0.200		67	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr) [0.0990		μg/l		0.200		50	30-150		
_CS (8021525-BS1)										
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Aroclor-1016	2.54		μg/l	0.200	2.50		101	50-114		
Aroclor-1016 [2C]	2.48		μg/l	0.200	2.50		99	50-114		
Aroclor-1260	2.52		μg/l	0.200	2.50		101	40-127		
Aroclor-1260 [2C]	2.19		μg/l	0.200	2.50		88	40-127		
Surrogate: Decachlorobiphenyl (Sr)	0.134		μg/l		0.200		67	30-150		
Surrogate: Decachlorobiphenyl (Sr) [2C]	0.131		μg/l		0.200		66	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr)	0.134		μg/l		0.200		67 52	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr) [:	0.106		μg/l		0.200		53	30-150		
.CS Dup (8021525-BSD1)										
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Aroclor-1016	2.50		μg/l	0.200	2.50		100	50-114	1	20
Aroclor-1016 [2C]	2.27		μg/l	0.200	2.50		91	50-114	9	20
Aroclor-1260	2.45		μg/l	0.200	2.50		98	40-127	3	20
Aroclor-1260 [2C]	2.29		μg/l	0.200	2.50		91	40-127	4	20
Surrogate: Decachlorobiphenyl (Sr)	0.130		μg/l		0.200		65	30-150		
Surrogate: Decachlorobiphenyl (Sr) [2C]	0.139		μg/l		0.200		70	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr)	0.133		μg/l		0.200		66 54	30-150 30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr) [:	0.107		μg/l		0.200		54	30-150		
	A74755-01									
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Aroclor-1016	2.41		μg/l	0.211	2.63	BRL	92	50-114		
Aroclor-1016 [2C]	2.37		μg/l	0.211	2.63	BRL	90	50-114		
Aroclor-1260	2.45		μg/l	0.211	2.63	BRL	93	40-127		
Aroclor-1260 [2C]	2.77		μg/l	0.211	2.63	BRL	105	40-127		
Surrogate: Decachlorobiphenyl (Sr)	0.135		μg/l		0.211		64	30-150		
Surrogate: Decachlorobiphenyl (Sr) [2C]	0.179		μg/l		0.211		85	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr)	0.136		μg/l		0.211		65	30-150		

Semivolatile Organic Compounds by GC - Quality Control

					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021525 - SW846 3510C										
Matrix Spike (8021525-MS1) Source: S	A74755-01									
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr) [0.102		μg/l		0.211		49	30-150		
Matrix Spike Dup (8021525-MSD1) Source: S	A74755-01									
Prepared: 25-Feb-08 Analyzed: 26-Feb-08										
Aroclor-1016	2.45		μg/l	0.211	2.63	BRL	93	50-114	2	15
Aroclor-1016 [2C]	2.39		μg/l	0.211	2.63	BRL	91	50-114	0.9	15
Aroclor-1260	2.53		μg/l	0.211	2.63	BRL	96	40-127	3	20
Aroclor-1260 [2C]	2.82		μg/l	0.211	2.63	BRL	107	40-127	1	20
Surrogate: Decachlorobiphenyl (Sr)	0.133		μg/l		0.211		63	30-150		
Surrogate: Decachlorobiphenyl (Sr) [2C]	0.191		μg/l		0.211		90	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr)	0.133		μg/l		0.211		63	30-150		
Surrogate: 4,4-DB-Octafluorobiphenyl (Sr) ['	0.100		μg/l		0.211		48	30-150		
	Extracta	ble Pet	roleum Hy	drocarbon	s - Quality	Control				
	Extracta	ble Pet	roleum Hy	drocarbon	s - Quality Spike	Control		%REC		RPD
Analyte(s)	Extracta Result	ble Pet	Units	vdrocarbon *RDL			%REC	%REC Limits	RPD	RPD Limit
Analyte(s) Batch 8021419 - SW846 3510C					Spike	Source	%REC		RPD	
• \					Spike	Source	%REC		RPD	
Batch 8021419 - SW846 3510C					Spike	Source	%REC		RPD	
Batch 8021419 - SW846 3510C Blank (8021419-BLK1)					Spike	Source	%REC		RPD	
Batch 8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM)	Result		Units	*RDL	Spike	Source	%REC		RPD	
Blank (8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM) LCS (8021419-BS1)	Result		Units	*RDL	Spike	Source	%REC		RPD	
Blank (8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM) LCS (8021419-BS1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08	Result		Units mg/l	*RDL	Spike Level	Source		Limits	RPD	
Batch 8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM) LCS (8021419-BS1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM)	Result BRL 23.4		Units	*RDL	Spike	Source	%REC		RPD	
Batch 8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM) LCS (8021419-BS1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM)	Result		Units mg/l	*RDL	Spike Level	Source		Limits	RPD	
Batch 8021419 - SW846 3510C Blank (8021419-BLK1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM) LCS (8021419-BS1) Prepared: 22-Feb-08 Analyzed: 24-Feb-08 Non-polar material (SGT-HEM)	Result BRL 23.4		Units mg/l	*RDL	Spike Level	Source		Limits	RPD	

Total Metals by EPA 200 Series Methods - Quality Control

					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021350 - SW846 3005A	L									
Blank (8021350-BLK1)										
Prepared: 22-Feb-08 Analyzed:	25-Feb-08									
Iron	BRL		mg/l	0.0550						
Chromium	BRL		mg/l	0.0080						
Cadmium	BRL		mg/l	0.0025						
Arsenic	BRL		mg/l	0.0040						
Silver	BRL		mg/l	0.0050						
LCS (8021350-BS1)										
Prepared: 22-Feb-08 Analyzed:	25-Feb-08									
Iron	1.81	QC2	mg/l	0.0550	1.25		145	85-115		
Silver	1.28		mg/l	0.0050	1.25		103	85-115		
Cadmium	1.34		mg/l	0.0025	1.25		107	85-115		
Arsenic	1.28		mg/l	0.0040	1.25		103	85-115		
Chromium	1.36		mg/l	0.0080	1.25		109	85-115		
<u>Duplicate (8021350-DUP1)</u>	Source: SA74713-03									
Prepared: 22-Feb-08 Analyzed: 2	25-Feb-08									
Iron	0.212	J	mg/l	0.255		0.250			17	20
Chromium	BRL		mg/l	0.0080		BRL				20
Cadmium	BRL		mg/l	0.0025		BRL				20
Silver	BRL		mg/l	0.0050		BRL				20
Arsenic	0.0048	QR8	mg/l	0.0040		0.0062			26	20
Matrix Spike (8021350-MS1)	Source: SA74755-01									
Prepared: 22-Feb-08 Analyzed: 2	25-Feb-08									
Iron	1.32		mg/l	0.0550	1.25	0.0511	101	70-130		
Chromium	1.26		mg/l	0.0080	1.25	BRL	101	70-130		
Cadmium	1.31		mg/l	0.0025	1.25	BRL	105	70-130		
Arsenic	1.34		mg/l	0.0040	1.25	BRL	107	70-130		
Silver	1.34		mg/l	0.0050	1.25	BRL	107	70-130		
Post Spike (8021350-PS1)	Source: SA74755-01									
Prepared: 22-Feb-08 Analyzed: 2	25-Feb-08									
Iron	2.70		mg/l		2.50	0.102	104	85-115		
Cadmium	2.63		mg/l		2.50	-0.0015	105	85-115		
Silver	2.72		mg/l		2.50	-0.0018	109	85-115		
Arsenic	2.70		mg/l		2.50	0.0016	108	85-115		
Chromium	2.65		mg/l		2.50	0.0012	106	85-115		

General Chemistry Parameters - Quality Control

	D. Iv	El	** **	*DDI	Spike	Source	0/PEG	%REC	n n n	RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021303 - General Prepar	ation									
Blank (8021303-BLK1) Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	BRL		mg/l	0.008						
Blank (8021303-BLK2) Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	BRL		mg/l	0.008						
LCS (8021303-BS1) Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	0.047		mg/l	0.008	0.0501		94	90-110		
LCS (8021303-BS2) Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	0.049		mg/l	0.008	0.0501		98	90-110		
Duplicate (8021303-DUP1) Prepared & Analyzed: 20-Feb-08	Source: SA74755-01									
Hexavalent Chromium	0.007	J	mg/l	800.0		0.006			15	20
Matrix Spike (8021303-MS1) Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	Source: SA74755-01 0.051		mg/l	0.008	0.0501	0.006	90	80-120		
Reference (8021303-SRM1)	5.55		9	0.000	0.000	0.000		00 .20		
Prepared & Analyzed: 20-Feb-08 Hexavalent Chromium	0.024		mg/l	0.008	0.0250		96	85-115		
Batch 8021304 - General Prepar	ation									
Blank (8021304-BLK1) Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	BRL		mg/l	0.020						
Blank (8021304-BLK2) Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	BRL		mg/l	0.020						
LCS (8021304-BS1) Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	0.055		mg/l	0.020	0.0500		110	90-110		
LCS (8021304-BS2) Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	0.054		mg/l	0.020	0.0500		108	90-110		
<u>Duplicate (8021304-DUP1)</u>	Source: SA74755-01									
Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	0.048		mg/l	0.020		0.045			6	20
Matrix Spike (8021304-MS1) Prepared & Analyzed: 20-Feb-08	Source: SA74755-01									
Total Residual Chlorine	0.096		mg/l	0.020	0.0500	0.045	102	80-120		
Reference (8021304-SRM1) Prepared & Analyzed: 20-Feb-08 Total Residual Chlorine	0.116		mg/l	0.020	0.120		96	85-115		
Batch 8021348 - General Prepar	ation									
Blank (8021348-BLK1)										

General Chemistry Parameters - Quality Control

					Spike	Source		%REC		RPD
Analyte(s)	Result	Flag	Units	*RDL	Level	Result	%REC	Limits	RPD	Limit
Batch 8021348 - General Preparation Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	BRL		mg/l	5.00						
Blank (8021348-BLK2)			3							
Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	BRL		mg/l	5.00						
Blank (8021348-BLK3) Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	BRL		mg/l	5.00						
·	ırce: SA74654-02									
Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	205		mg/l	25.0		205			0	20
Reference (8021348-SRM1) Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	94.0		mg/l	10.0	90.4		104	91-109		
Reference (8021348-SRM2) Prepared & Analyzed: 21-Feb-08	20.0		/I	40.0	00.4		07	04.400		
Total Suspended Solids Reference (8021348-SRM3)	88.0		mg/l	10.0	90.4		97	91-109		
Prepared & Analyzed: 21-Feb-08 Total Suspended Solids	90.0		mg/l	10.0	90.4		100	91-109		
Batch 8021402 - General Preparation										
Blank (8021402-BLK1) Prepared: 21-Feb-08 Analyzed: 22-Feb- Cyanide (total)	08 BRL		mg/l	0.0100						
LCS (8021402-BS1) Prepared: 21-Feb-08 Analyzed: 22-Feb-Cyanide (total)	08 0.318		mg/l	0.0100	0.300		106	90-110		
Matrix Spike (8021402-MS1) Sou Prepared: 21-Feb-08 Analyzed: 22-Feb-	urce: SA74713-01		J							
Cyanide (total)	0.323		mg/l	0.0100	0.300	0.0119	104	90-110		
Matrix Spike Dup (8021402-MSD1) Sou Prepared: 21-Feb-08 Analyzed: 22-Feb-	08									
Cyanide (total)	0.334		mg/l	0.0100	0.300	0.0119	107	90-110	3	20
Reference (8021402-SRM1) Prepared: 21-Feb-08 Analyzed: 22-Feb-Cyanide (total)	0.513		mg/l	0.0100	0.495		104	58.6-142.2		

Notes and Definitions

J

QC1	Analyte out of acceptance range.
QC2	Analyte out of acceptance range in QC spike but no reportable concentration present in sample.
QR2	The RPD result exceeded the QC control limits; however, both percent recoveries were acceptable. Sample results for the QC batch were accepted based on percent recoveries and completeness of QC data.
QR8	Analyses are not controlled on RPD values from sample concentrations that are less than 5 times the reporting level. The batch is accepted based upon the difference between the sample and duplicate is less than or equal to the reporting limit.
BRL	Below Reporting Limit - Analyte NOT DETECTED at or above the reporting limit
dry	Sample results reported on a dry weight basis
NR	Not Reported
RPD	Relative Percent Difference

A plus sign (+) in the Method Reference column indicates the method is not accredited by NELAC.

Interpretation of Total Petroleum Hydrocarbon Report

Petroleum identification is determined by comparing the GC fingerprint obtained from the sample with a library of GC fingerprints obtained from analyses of various petroleum products. Possible match categories are as follows:

Detected but below the Reporting Limit; therefore, result is an estimated concentration (CLP J-Flag).

Gasoline - includes regular, unleaded, premium, etc.

Fuel Oil #2 - includes home heating oil, #2 fuel oil, and diesel

Fuel Oil #4 - includes #4 fuel oil

Fuel Oil #6 - includes #6 fuel oil and bunker "C" oil

Motor Oil - includes virgin, waste automobile oil and hydraulic oil

Ligroin - includes mineral spirits, petroleum naphtha, vm&p naphtha

Aviation Fuel - includes kerosene, Jet A and JP-4

Other Oil - includes lubricating and cutting oil, and silicon oil

At times, the unidentified petroleum product is quantified using a calibration that most closely approximates the distribution of compounds in the sample. When this occurs, the result is qualified as *TPH (Calculated as).

<u>Laboratory Control Sample (LCS)</u>: A known matrix spiked with compound(s) representative of the target analytes, which is used to document laboratory performance.

Matrix Duplicate: An intra-laboratory split sample which is used to document the precision of a method in a given sample matrix.

<u>Matrix Spike</u>: An aliquot of a sample spiked with a known concentration of target analyte(s). The spiking occurs prior to sample preparation and analysis. A matrix spike is used to document the bias of a method in a given sample matrix.

<u>Method Blank</u>: An analyte-free matrix to which all reagents are added in the same volumes or proportions as used in sample processing. The method blank should be carried through the complete sample preparation and analytical procedure. The method blank is used to document contamination resulting from the analytical process.

<u>Method Detection Limit (MDL)</u>: The minimum concentration of a substance that can be measured and reported with 99% confidence that the analyte concentration is greater than zero and is determined from analysis of a sample in a given matrix type containing the analyte.

Reportable Detection Limit (RDL): The lowest concentration that can be reliably achieved within specified limits of precision and accuracy during routine laboratory operating conditions. For many analytes the RDL analyte concentration is selected as the lowest non-zero standard in the calibration curve. While the RDL is approximately 5 to 10 times the MDL, the RDL for each sample takes into account the sample volume/weight, extract/digestate volume, cleanup procedures and, if applicable, dry weight correction. Sample RDLs are highly matrix-dependent.

<u>Surrogate</u>: An organic compound which is similar to the target analyte(s) in chemical composition and behavior in the analytical process, but which is not normally found in environmental samples. These compounds are spiked into all blanks, standards, and samples prior to analysis. Percent recoveries are calculated for each surrogate.

Validated by: Hanibal C. Tayeh, Ph.D. June O'Connor Rebecca Merz



HANTRAL TECHNOLOGY

CHAIN OF CUSTODY RECORD

Page ___(_of____}

Special Handling:

Standard TAT (7 to 10 business days

Rush TAT - Date Needed:

All TATs subject to laboratory approval.

Min. 24-hour notification needed for rushes.

Samples disposed of after 60 days unless otherwise instructed.

Report To: Dimitr. GOWNIS			Invoi	ce To	-T	<u>etra</u> Gr	le ant	ch St	R(Z) free:	zo_ €		-	Site Name: Brigham House								
												Location: 341 Ht. Nulsun St. Watertown State: MA									
Project Mgr.: _	<u> </u>		P.O. 1	No.: _	1270	100	3.	RQ	N:_			_	Sam	pler(s	s):	D	in.t	Ti	6	2 اللماد	
1=Na ₂ S2O ₃ 2	=HCl 3=H ₂ SO ₄ :NaHSO ₄ 9=	4=HNO ₃ 5=Na	OH 6=Ascor					Со	ntain	ers:		1	CP		Analy	/ses:				1000000000	rting Notes: fneeded)
O-Oil SW-S	Water GW=Gro	D-Soil SL-Sli	udge A=Air			ve.	Vials	# of Amber Glass	Glass		Coop	200	E06/28	608	20	PAIRS	Phenola	mile	100	Provide CT DPI	porting Level
	G=Grab C=] ,	rvati	VO	mbe	lear	of Plastic	2	2 5	-	Ø	IJ	PA		1	2		□ No QC
Lab Id:	Sample Id:	Date:	Time:	Type	Matrix	Preservative	# of VOA Vials	# of A	# of Clear Glass	# of P	TPA	Hest	504	PCB	624	8970	823	TSHE	7.35	State specific re	porting standards; DES Permit
475501	Crawl Spece	2/20/08	11:00	G	GW	4				3		V								* wetals in	clude
				1	1	1	3						V								Cd, Cr, Fe
				H	-	9	_	1						V	_			_	4		
	313			+		2	3							-	1	-/			+		·
		7.		₩	H	9		2					-	-	-		./		+	, ,	
				+	H	3		o.		1				-	\dashv		V	V			
				†	H	9	1 1 1		1/3	1									1		
				Ħ	Ħ	9				1									1	/	277
	V	1	1	V	V	3		2		*	V		-								
			I	200		-	nqui	shed	by:					R	eceiv	ed by	y:	100	1	Date:	Time:
	when available to (5 1	m		,(11	Q.	lou	m	2	.24	igo ^r	1/2	Ž	16	, se	- <i>i</i>			2/20/08	1347
EDD Format	pdf, xl	s, hs Acc	en	6	14	H	22	À	,			4	Sti	10	41	Bé	w	lv	0	2/20/08	5:42pm
Condition upon r	receipt: 🗆 loed 🗆	Ambient □°C	5.5		J	62.77							- arjan			7711	D. j ff.	21,00			